

#### **TERMINYL**

TE Internal #: 324084

Ring Terminals & Spade Terminals, Ring Tongue, 00 AWG Wire Size, 60.6 – 76.3 mm<sup>2</sup> Wire Size, 119500 – 150500 CMA Wire Size,

Stud Size 3/8

View on TE.com >



Terminals & Splices > Ring Terminals & Spade Terminals











Ring & Spade Terminal Type: Ring Tongue

Wire Size: 119500 – 150500 CMA

Stud Size: 3/8

### **Features**

### **Product Type Features**

Shape Description	RING-047
Stud Size	3/8
Sealable	No
Wire Insulation Support Retention Type	Insulation Support

## **Configuration Features**

Number of Holes	1
Terminal Angle	180°

## **Body Features**

Inspection Slot	No
Insulation Sleeve Color	Yellow
Weight per Piece	32.635 g
Stripe Color	Yellow

#### **Contact Features**

Ring & Spade Terminal Type	Ring Tongue
Barrel Type	Closed



Terminal Orientation	Straight
Terminal Plating Material	Tin
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	119500 – 150500 CMA
Stud Diameter	9.91 mm[.39 in]
Tongue Thickness	.79 mm[.031 in]
Overall Product Length	61.37 mm[2.416 in]
Accepts Wire Insulation Diameter (Max)	15.49 mm[.61 in]
Accepts Wire Insulation Diameter Range	15.49 mm[.61 in]
Usage Conditions	
Usage Conditions  Insulation Option	Partially Insulated
	Partially Insulated  105 °C[221 °F]
Insulation Option	
Insulation Option Operating Temperature Range	
Insulation Option Operating Temperature Range Operation/Application	105 °C[221 °F]
Insulation Option Operating Temperature Range Operation/Application Compatible With Wire Base Material	105 °C[221 °F]  Copper
Insulation Option Operating Temperature Range Operation/Application Compatible With Wire Base Material Compatible With Wire Plating Material	105 °C[221 °F]  Copper  Tin
Insulation Option Operating Temperature Range Operation/Application Compatible With Wire Base Material Compatible With Wire Plating Material Heavy Duty	105 °C[221 °F]  Copper  Tin
Insulation Option Operating Temperature Range Operation/Application Compatible With Wire Base Material Compatible With Wire Plating Material Heavy Duty Industry Standards	105 °C[221 °F]  Copper  Tin  No
Insulation Option Operating Temperature Range Operation/Application Compatible With Wire Base Material Compatible With Wire Plating Material Heavy Duty Industry Standards Government Qualified	105 °C[221 °F]  Copper  Tin  No

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224)



Does not contain REACH SVHC

Low Halogen - Br, Cl, F, I < 900 ppm per
homogenous material. Also BFR/CFR/PVC
Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



#### **Documents**

**Product Drawings** 

**TERMINAL,T-N R 2/0 3/8** 

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_324084\_L.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_324084\_L.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_324084\_L.3d\_stp.zip

English



**Customer View Model** 

ENG\_CVM\_324084\_F.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_324084\_F.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_324084\_F.2d\_dxf.zip

English

3D PDF

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

RADIATION\_RESISTANT\_PRE-INSULATED\_TERMINALS\_SPLICES

English

Standard Terminals & Splices

English