PLASTI-GRIP

TE Internal #: 342143-1

Ring Terminals & Spade Terminals, Ring Tongue, 16 – 14 AWG Wire Size, 1 – 2.5 mm² Wire Size, Stud Size #8 / M4, PLASTI-GRIP

View on TE.com >



Terminals & Splices > Ring Terminals & Spade Terminals











Ring & Spade Terminal Type: Ring Tongue

Wire Size: 1 – 2.5 mm²
Stud Size: #8, M4

Stud Diameter: 4.3 mm [.171 in]

Features

Product Type Features

Terminal Features	Sheared
Shape Description	RING-043
Stud Size	#8, M4
Sealable	No
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	1
Terminal Angle	180°
Electrical Characteristics	
Voltage (Max)	600 V
Body Features	

No

Blue

.891 g

Blue

Inspection Slot

Weight per Piece

Stripe Color

Insulation Sleeve Color



Contact Features

Ring & Spade Terminal Type	Ring Tongue
Barrel Type	Closed
Terminal Orientation	Offset
Terminal Plating Material	Tin

Mechanical Attachment

Wire Insulation Support	Without	

Dimensions

Wire Size	1 – 2.5 mm ²
Stud Diameter	4.3 mm[.171 in]
Tongue Thickness	.79 mm[.031 in]
Overall Product Length	22.1 mm[.87 in]
Accepts Wire Insulation Diameter (Max)	4.9 mm[.193 in]
Accepts Wire Insulation Diameter Range	3 – 4.9 mm[.118 – .193 in]

Usage Conditions

Insulation Option	Partially Insulated
Operating Temperature Range	105 °C[221 °F]

Operation/Application

Compatible With Wire Base Material	Copper
Compatible With Wire Plating Material	Tin
Heavy Duty	No

Industry Standards

Government Qualified	No	

Packaging Features

Packaging Quantity	100
Packaging Method	Loose Piece

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold



Halogen Content Not Low Halogen - contains Br or Cl > 900	EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
ppm.	Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.

Product Compliance Disclaimer

Solder Process Capability

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Not applicable for solder process capability







Also in the Series | PLASTI-GRIP









Crimp Wire Pins, Tabs & Ferrules(25)



Ring Terminals & Spade Terminals(537)



Documents

Product Drawings

16-14 F.E.P.G. R/TONGUE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_342143-1_N.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_342143-1_N.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_342143-1_N.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

MD_342143-1_05092018951_dmtec

English

MD_342143-1_05092018951_dmtec

English