
35492 - ACTIVE

PLASTI-GRIP

TE Internal #: 35492 Ring Terminals & Spade Terminals, Ring Tongue, 12 – 10 AWG Wire Size, 2.62 – 6.64 mm² Wire Size, 5180 – 13100 CMA Wire Size, PLASTI-GRIP

View on TE.com >

Terminals & Splices > Ring Terminals & Spade Terminals



Ring & Spade Terminal Type: Ring Tongue

Wire Size: 5180 – 13100 CMA

Stud Size: 1/4, M6

Features

Product Type Features



| Shape Description | RING-043 |
|--|--------------------|
| Stud Size | 1/4, M6 |
| Sealable | No |
| Wire Insulation Support Retention Type | Insulation Support |
| Configuration Features | |
| Number of Holes | 1 |
| Terminal Angle | 180 ° |
| Electrical Characteristics | |
| Voltage (Max) | 600 V |
| Body Features | |
| Inspection Slot | No |
| Weight per Piece | .409 g |
| Contact Features | |
| Ring & Spade Terminal Type | Ring Tongue |
| Barrel Type | Closed |
| | |

35492

Ring Terminals & Spade Terminals, Ring Tongue, 12 – 10 AWG Wire Size, 2.62 – 6.64 mm² Wire Size, 5180 – 13100 CMA Wire Size, PLASTI-GRIP



| Terminal Orientation | Offset | |
|---|---|--|
| Terminal Plating Material | Tin | |
| Mechanical Attachment | | |
| Wire Insulation Support | With | |
| Dimensions | | |
| Wire Size | 5180 – 13100 CMA | |
| Stud Diameter | 6.73 mm[.265 in] | |
| Tongue Thickness | 1.02 mm[.04 in] | |
| Overall Product Length | 31.67 mm[1.25 in] | |
| Accepts Wire Insulation Diameter (Max) | 7.62 mm[.3 in] | |
| Accepts Wire Insulation Diameter Range | 7.62 mm[.3 in] | |
| Usage Conditions | | |
| Insulation Option | Partially Insulated | |
| Operating Temperature Range | 105 °C[221 °F] | |
| Operation/Application | | |
| Compatible With Wire Base Material | Copper | |
| Compatible With Wire Plating Material | Tin | |
| Heavy Duty | No | |
| Industry Standards | | |
| Government Qualified | No | |
| Packaging Features | | |
| Packaging Quantity | 500 | |
| Packaging Method | Loose Piece | |
| Product Compliance | | |
| Product Compliance For compliance documentation, visit the product page on TE.com> | | |
| EU RoHS Directive 2011/65/EU | Compliant | |
| EU ELV Directive 2000/53/EC | Compliant | |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold | |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) | |

35492

Ring Terminals & Spade Terminals, Ring Tongue, 12 – 10 AWG Wire Size, 2.62 – 6.64 mm² Wire Size, 5180 – 13100 CMA Wire Size, PLASTI-GRIP



Does not contain REACH SVHC

Not Low Halogen - contains Br or Cl > 900 ppm.

Solder Process Capability


Halogen Content

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | PLASTI-GRIP

| Compression Connectors(3) | Crimp Wire Pins, Tabs & Ferrules(25) | Ring Terminals & Spade Terminals(537) | Splices(49) |
|---------------------------|--------------------------------------|---------------------------------------|-------------|

35492

Ring Terminals & Spade Terminals, Ring Tongue, 12 – 10 AWG Wire Size, 2.62 – 6.64 mm² Wire Size, 5180 – 13100 CMA Wire Size, PLASTI-GRIP



Documents

Product Drawings PG RING 12-10 1/4 STUD

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_35492_W.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_35492_W.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_35492_W.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications Application Specification

English

Agency Approvals

UL Report

English