SSR-480D50 V ACTIVE

Potter & Brumfield | Potter & Brumfield SSR

TE Internal #: 3-1393030-1 Power Relays, Solid State, 1 Form A (SPST-NO), Chassis Mount, Potter & Brumfield SSR

View on TE.com >



Relays, Contactors & Switches > Relays > Power Relays > P&B SSR SERIES SOLID STATE RELAYS





Power Relay Type: Solid State

Contact Arrangement: 1 Form A (SPST-NO)

Relay Mounting Type: Chassis Mount

All P&B SSR SERIES SOLID STATE RELAYS (10)

Features

| Product Type Features | |
|-------------------------------------------------------|---------------|
| Output Type | AC |
| Power Relay Type | Solid State |
| Configuration Features | |
| Output Switching | Zero |
| Electrical Characteristics | |
| Input Voltage Typical | 4 – 32 VDC |
| Output Voltage (Max) | 660 V |
| Output Voltage Rating (AC Relays) | 48 – 660 Vrms |
| Output Current Rating | .1 – 50 Arms |
| Output Current (Min) | .1 A |
| Insulation Initial Dielectric Between Contacts & Coil | 4000 Vrms |

| Product Weight | 98 g[3.45 oz] |
|----------------|---------------|
| Case Color | Black |

SSR-480D50

Power Relays, Solid State, 1 Form A (SPST-NO), Chassis Mount, Potter & Brumfield SSR



Contact Features

| Switch Arrangement | 1 Form A (SPST-NO) |
|--------------------------------------|-----------------------------------------------|
| Contact Arrangement | 1 Form A (SPST-NO) |
| Termination Features | |
| Relay Termination Type | Screws |
| Mechanical Attachment | |
| Coupling | Optical |
| Relay Mounting Type | Chassis Mount |
| Housing Features | |
| Relay Housing Style | Hockey Puck |
| Dimensions | |
| Dimensions (L x W x H) (Approximate) | 45 x 57.8 x 43.4 mm[1.772 x 2.276 x 1.709 in] |
| Usage Conditions | |
| Operating Temperature Range | -30 - 80 °C |
| Operation/Application | |
| R-Switch & slimSSR Relays | No |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant with Exemptions |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| EU ELV Directive 2000/53/EC | Compliant with Exemptions |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) SVHC > Threshold: Pb (88% in Component Part) Aticle Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location. |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not applicable for solder process capability |

Product Compliance Disclaimer

SSR-480D50

Power Relays, Solid State, 1 Form A (SPST-NO), Chassis Mount, Potter & Brumfield SSR



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Potter & Brumfield SSR



Documents

CAD Files

Customer View Model ENG_CVM_CVM_3-1393030-1_B1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-1393030-1_B1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_3-1393030-1_B1.2d_dxf.zip

English

3D PDF

3D

SSR-480D50

Power Relays, Solid State, 1 Form A (SPST-NO), Chassis Mount, Potter & Brumfield SSR



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages SSR Hockey Puck Solid State Relay With Paired SCR Output English

SSR, SSRD and SSRT Series

English