# NC6-P108-04 ~ ACTIVE

## Buchanan | Buchanan NC6 TE Internal #: 3-1437664-3 Barrier Strips, Dual Barrier, Printed Circuit Pin, Wire-to-Board, 4 Position, 9.53 mm [.375 in] Centerline, 1 Row, 300 V, Buchanan NC6 View on TE.com >



Connectors > Terminal Blocks & Strips > Barrier Strips



Barrier Strip Style: Dual Barrier

Bottom Termination Type: Printed Circuit Pin

Connector System: Wire-to-Board

Number of Positions: 4

Centerline (Pitch): 9.53 mm [.375 in ]

## Features

## Product Type Features

Profile	Low
Product Type	Barrier Strip
Block Style	Flat
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Levels	1
Number of Positions	4
Number of Rows	1
Electrical Characteristics	
Current Rating (Max)	20 A
Voltage Rating	300 V
Body Features	
Color	Black

## NC6-P108-04

Barrier Strips, Dual Barrier, Printed Circuit Pin, Wire-to-Board, 4 Position, 9.53 mm [. 375 in] Centerline, 1 Row, 300 V, Buchanan NC6



Barrier Strip Style	Dual Barrier
Contact Features	
Terminal Material	Copper Alloy
Terminal Plating Material	Tin
Contact Current Rating (Max)	20 A
Termination Features	
Bottom Termination Type	Printed Circuit Pin
Mechanical Attachment	
Mounting Angle	Vertical
Screw Head Type	Wire Clamp Combo Head
Top Termination Type	Wire Clamp Combo Head
Mounting Insert	Without
Screw Plating Material	Zinc
Screw Material	Steel
Mounting Options	None
Mounting Bushing	With
Mounting Ears	Without
Screw Size	6-32
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Polyamide
Centerline (Pitch)	9.53 mm[.375 in]
Dimensions	
Length	39.65 mm[1.561 in]
Wire Size	.3 – 3 mm²
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	

**C** For support call+1 800 522 6752

### NC6-P108-04

Barrier Strips, Dual Barrier, Printed Circuit Pin, Wire-to-Board, 4 Position, 9.53 mm [. 375 in] Centerline, 1 Row, 300 V, Buchanan NC6



Packaging Quantity	45
Packaging Method	Package
Other	
Comment	Do not order screw and captive clamp in combination with other top hardware., Other options available upon request, consult our Product Information Center.

## Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

#### 1100

#### Solder Process Capability

#### Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**


### NC6-P108-04

Barrier Strips, Dual Barrier, Printed Circuit Pin, Wire-to-Board, 4 Position, 9.53 mm [. 375 in] Centerline, 1 Row, 300 V, Buchanan NC6





Also in the Series | Buchanan NC6



## Documents

Product Drawings NC6-P108-04=7180XX002/30

English

#### **CAD** Files

**Customer View Model** 

ENG\_CVM\_CVM\_3-1437664-3\_M1.3d\_stp.zip

English

Customer View Model

ENG\_CVM\_CVM\_3-1437664-3\_M1.2d\_dxf.zip

English

#### 3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_3-1437664-3\_M1.3d\_igs.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages BUCHANAN TERMINAL BLOCKS CATALOG - BARRIER STRIPS

English

1-1773458-2\_BARRIER\_STRIPS\_QUICK\_REFERENCE\_GUIDE

English