3-1903389-4 V ACTIVE

GRACE INERTIA 2.5

TE Internal #: 3-1903389-4

Rectangular Connector Housings, Wire-to-Wire, 3 Position, .098 in [2.5 mm] Centerline, 1 Row, PBT GF, Plug, Socket, Wire & Cable,

GRACE INERTIA 2.5

View on TE.com >



Connectors > Rectangular Connectors > Rectangular Connector Housings > STD Temp Sig GRACE INERTIA Plug











Connector System: Wire-to-Wire

Number of Positions: 3

Centerline (Pitch): 2.5 mm [.098 in]

Number of Rows: 1

Housing Material: PBT GF

All STD Temp Sig GRACE INERTIA Plug (63)

Features

Product Type Features

Connector System	Wire-to-Wire
Connector & Housing Type	Plug
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Connector Type	Housing
Product Type	Connector
Glow Wire Rating	Standard Part - Not Glow Wire
Configuration Features	
Number of Cavities	3
Number of Positions	3
Number of Positions Number of Rows	31



Electrical Characteristics

Electrical Characteristics	
Operating Voltage	250 VDC
Contact Features	
Contact Layout	Inline
Multiple Contact Types	Without
Shunts/Shorting Bars	Without
Contact Type	Socket
Mechanical Attachment	
Panel Mount	No
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	2.5 mm[.098 in]
Housing Material	PBT GF
Housing Color	Yellow
Dimensions	
Height	11 mm[.433 in]
Length	11.2 mm[.441 in]
Width	9.6 mm[.378 in]
Usage Conditions	
Operating Temperature Range	-30 - 105 °C[-22 - 221 °F]
Operation/Application	
Assembly Integration Feature	Without
Halogen Free	No
Circuit Application	Signal
For Use With	Receptacle Housing
Identification Marking	
Circuit Identification Feature	Without
Packaging Features	
Packaging Quantity	1000
Packaging Method	Bag

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Also in the Series | GRACE INERTIA 2.5









PCB Headers & Receptacles(138)



PCB Latches, Locks & Retainers(5)



Rectangular Connector Housings(49)



Rectangular Connector Locking(2)



Rectangular Power Connectors(35)



Wire-to-Board Connector Assemblies & Housings(72)



Documents

Product Drawings

GIC 2.5 W PLUG HSG 3P YELLOW

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-1903389-4_G_c-3-1903389-4-g.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-1903389-4_G_c-3-1903389-4-g.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-1903389-4_G_c-3-1903389-4-g.3d_stp.zip

English

Product Specifications

Product Specification

English