
3-2172070-2 - ACTIVE

TE Internal #: 3-2172070-2 Standard Circular Connectors, Wire-to-Board, 4 Position, Sealable, Signal, Panel Mount, Reverse Gender, Nickel, Brass, A Polarization Code, Polyamide

View on TE.com >



Connectors > Circular Connectors > Standard Circular Connectors



Connector System: Wire-to-Board

Number of Positions: 4

Sealable: Yes

Contact Current Rating (Max): 4A

Circuit Application: Signal

Features

Product Type Features

Product Type	Connector
Connector System	Wire-to-Board
Sealable	Yes
Circular Connector Type	Receptacle
Shell Type	Metal
Configuration Features	
Number of Positions	4
Number of Power Positions	0
Number of Signal Positions	4
Contacts Preloaded	Yes
Body Features	
Shell Plating Material	Nickel
Shell Base Material	Brass
Circular Connector Insulation Material Type	Polyamide

3-2172070-2

Standard Circular Connectors, Wire-to-Board, 4 Position, Sealable, Signal, Panel Mount, Reverse Gender, Nickel, Brass, A Polarization Code, Polyamide



Contact Features

Contact Current Rating (Max)	4 A
Reverse Gender	Yes
Contact Layout Arrangement	Circular
Circular Connector Contact Type	Pin
Mechanical Attachment	
Connector Mounting Type	Panel Mount
Polarization Code	A
Mating Alignment Type	Keyed
Mating Retention	With
Housing Features	
Circular Connector Shell Size	12
Usage Conditions	
IP Water Sealing Level	8
IP Dust Sealing Level	6
Operating Temperature Range	-40 – 80 °C[-40 – 176 °F]

Operation/Application

Circuit Application	Signal
Shielded	No
Product Compliance	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) SVHC > Threshold: Pb (4% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

3-2172070-2

Standard Circular Connectors, Wire-to-Board, 4 Position, Sealable, Signal, Panel Mount, Reverse Gender, Nickel, Brass, A Polarization Code, Polyamide



Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # T4110001041-000 M12,FEMALE,STRAIGHT,A CODE,4P, PG7,GOLD

Documents

Product Drawings M12.MALE.PNLREAR.ACODE.4P.PCBSTAND.STRT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_3-2172070-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_3-2172070-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_3-2172070-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages M8 / M12 Connector System Catalog

C For support call+1 800 522 6752

3-2172070-2

Standard Circular Connectors, Wire-to-Board, 4 Position, Sealable, Signal, Panel Mount, Reverse Gender, Nickel, Brass, A Polarization Code, Polyamide



English

Product Specifications Application Specification

English