485043-1 - ACTIVE

SPLICE

TE Internal #: 485043-1 Splices, 4000 – 9000 CMA Wire Size, Brass, Pigtail Splice / Thru Splice Splice, Serrated, 4 Serration, Length 6.35 mm [.25 in], Reel, Open, SPLICE

View on TE.com >

Terminals & Splices > Splices



Sealable: No Wire Size: 4000 – 9000 CMA

Primary Product Material: Brass

Splice Type: Pigtail Splice, Thru Splice

Terminal Material Thickness: .51 mm [.02 in]

Features



Product Type Features

Barrel Style	Standard
Sealable	No
Splice Type	Pigtail Splice, Thru Splice
Serrated	Yes
Compatible With Discrete Wire Type	Solid, Stranded
Wire Insulation Support Retention Type	Non-Insulation Support
Configuration Features	
Number of Serrations	4
Compatible With Wire & Cable Type	Discrete Wire
Body Features	
Weight per Piece	.298 g[.01 oz]
Plating Material	Unplated
Primary Product Material	Brass
Contact Features	

485043-1

Splices, 4000 – 9000 CMA Wire Size, Brass, Pigtail Splice / Thru Splice Splice, Serrated, 4 Serration, Length 6.35 mm [.25 in], Reel, Open, SPLICE



Barrel Type	Open
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	4000 – 9000 CMA
Terminal Material Thickness	.51 mm[.02 in]
Overall Product Length	6.35 mm[.25 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-40 - 110 °C[-40 - 230 °F]
Operation/Application	
Heavy Duty	No
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	2500

Packaging Quantity	2500
Packaging Method	Reel

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

485043-1


Splices, 4000 – 9000 CMA Wire Size, Brass, Pigtail Splice / Thru Splice Splice, Serrated, 4 Serration, Length 6.35 mm [.25 in], Reel, Open, SPLICE





Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts







Also in the Series | SPLICE

485043-1

Splices, 4000 – 9000 CMA Wire Size, Brass, Pigtail Splice / Thru Splice Splice, Serrated, 4 Serration, Length 6.35 mm [.25 in], Reel, Open, SPLICE





Documents

Product Drawings SPLICE 4000-9000 .020 BR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_485043-1_AG_c-485043-1-ag.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_485043-1_AG_c-485043-1-ag.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_485043-1_AG_c-485043-1-ag.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance MD_485043-1_01292018329_dmtec

English

MD_485043-1_01292018329_dmtec

English

Agency Approvals CSA Certificate

English