

TE Internal #: 487544-3

FFC Connectors, Housing, Wire-to-Board, 6 Position, 1.27 mm [.05 in] Centerline, 1 Row, Socket, Package, Mating Retention, Wire &

Cable, Normal

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > FFC Connectors > FFC Receptacle Housing: 1.27mm











FFC Connector Product Type: Housing

Connector System: Wire-to-Board

Number of Positions: 6

Centerline (Pitch): 1.27 mm [.05 in]

Number of Rows: 1

All FFC Receptacle Housing: 1.27mm (52)

Features

Product Type Features

Troduct Type realures	
Connector & Housing Type	Receptacle
FFC Connector Product Type	Housing
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Insertion Force Type	Normal
Configuration Features	
Compatible With Wire & Cable Type	FFC
Number of Positions	6
Number of Rows	1
Electrical Characteristics	
Dielectric Withstanding Voltage (Max)	300 VAC

 $5000~\mathrm{M}\Omega$

Insulation Resistance



Contact Features Contact Type Socket Mechanical Attachment Mating Retention Type Detent Window Mating Retention Mating Retention Mating Retention Mating Retention Mating Retention Mating Retention Mating Alignment Panel Mount Feature Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Polyester Centerline (Pitch) 1,27 mm/ (05 in) FFC Cable Entry Straight Housing Color Black Usage Conditions Operating Temperature Range -55 = 105 °C(-67 - 221 °F) Operating Temperature Range Lu Flammability Rating UL Plammability Rating UL Pavy O Packaging Features Packaging Guantity 1 Packaging Method Other Note 1: Plain housings are side-to-side stackable on either straight or right angle posts unknowleded Amphorous quanting housings must be removed to provide housing end clearance		
Mechanical Attachment Mating Retention Type Detent Window Mating Retention With Mating Alignment Without Panel Mount Feature Without Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Polyester Centelline (Pitch) 1.27 mm [05 in] FFC Cable Entry Straight Housing Color Black Usage Conditions Operating Temperature Range -55 - 105 °C[67 - 221 °F] Operation/Application Circuit Application Signal Industry Standards UL Planmability Rating UL 9/IV-0 Packaging Features Packaging Gouantity 1 Packaging Method Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Operating Voltage	100 VAC
Mechanical Attachment Mating Retention Type Detent Window Mating Retention With Mating Alignment Without Panel Mount Feature Connector Mounting Type Cable Mount (Free Hanging) Housing Features Housing Material Polyester Centerline (Pitch) 1.27 mm[.05 in] 11 C Cable Lntry Straight 11 council Connector Mounting Type Black Usage Conditions Operating Temperature Range -55 – 105 "C[-67 – 221 "F] Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL 94V 0 Packaging Features Packaging Guantity 1 Packaging Method Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Contact Features	
Mating Retention Type Mating Retention Mating Alignment Without Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Polyester Centerline (Pitch) 1.27 mm(.05 in] FFC Cable Entry Straight Housing Color Black Usage Conditions Operating Temperature Range -55 = 105 °C[-6/ - 221 °T] Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL 94V-0 Packaging Guantity 1 Packaging Method Other Comment Note 1: Plain housings are side to side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Contact Type	Socket
Mating Retention Mating Alignment Without Panel Mount Feature Connector Mounting Type Housing Features Housing Material Centerline (Pitch) 1.27 mm[.05 in] FFC Cable Entry Straight Housing Color Black Usage Conditions Operating Temperature Range -55 - 105 °C[-67 - 221 °F] Operation/Application Circuit Application Signal Industry Standards UI P4V 0 Packaging Features Packaging Guantity 1 Packaging Method Packaging Method Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Mechanical Attachment	
Mating Alignment Without Panel Mount Feature Without Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Polyester Centerline (Pitch) 1.27 mm[.05 in] FFC Cable Entry Straight Housing Color Black Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Mating Retention Type	Detent Window
Panel Mount Feature Without Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Polyester Centerline (Pitch) 1.27 mm[.05 in] FEC Cable Entry Straight Housing Color Black Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operating Temperature Range Signal Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unstrouded AMPMODIU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Mating Retention	With
Connector Mounting Type Cable Mount (Free-Hanging) Housing Features Housing Material Polyester Centerline (Pitch) 1.27 mm[.05 in] FFC Cable Entry Straight Housing Color Black Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Mating Alignment	Without
Housing Features Housing Material Polyester Centerline (Pitch) 1.27 mm[.05 in] FFC Cable Entry Straight Housing Color Black Usage Conditions Operating Temperature Range -55 - 105 °C[-67 - 221 °F] Operation/Application Circuit Application Signal Industry Standards UL Planmability Rating UL 94V 0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Panel Mount Feature	Without
Housing Material Centerline (Pitch) 1.27 rmm[.05 in] FFC Cable Entry Straight Housing Color Black Usage Conditions Operating Temperature Range Operation/Application Circuit Application Signal Industry Standards UI. Flammability Rating UI. 94V-0 Packaging Features Packaging Quantity Packaging Method Other Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Connector Mounting Type	Cable Mount (Free-Hanging)
Centerline (Pitch) 1.27 mm[.05 in] FFC Cable Entry Straight Housing Color Black Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Note 1: Plain housings are side-to-side stackable on either straight or right angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Housing Features	
FFC Cable Entry Housing Color Black Usage Conditions Operating Temperature Range Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Housing Material	Polyester
Housing Color Usage Conditions Operating Temperature Range -55 - 105 °C[-67 - 221 °F] Operation/Application Circuit Application Signal Industry Standards UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Other Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Centerline (Pitch)	1.27 mm[.05 in]
Usage Conditions Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Other Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	FFC Cable Entry	Straight
Operating Temperature Range -55 – 105 °C[-67 – 221 °F] Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Housing Color	Black
Operation/Application Circuit Application Signal Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Usage Conditions	
Circuit Application Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Industry Standards UL Flammability Rating UL 94V-0 Packaging Features Packaging Quantity 1 Packaging Method Package Other Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Operation/Application	
UL Flammability Rating Packaging Features Packaging Quantity Packaging Method Package Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Circuit Application	Signal
Packaging Features Packaging Quantity Packaging Method Package Other Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Industry Standards	
Packaging Quantity Packaging Method Package Other Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	UL Flammability Rating	UL 94V-0
Packaging Method Other Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Packaging Features	
Other Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Packaging Quantity	1
Comment Note 1: Plain housings are side-to-side stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Packaging Method	Package
stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide	Other	
	Comment	stackable on either straight or right-angle post, unshrouded AMPMODU System 50 headers, Note 2: For end-to-end stacking, the posts located between the adjoining housings must be removed to provide

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

















Documents



Product Drawings

006 HOUSING FFC RCPT 050CL SR

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_487544-3_Z.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_487544-3_Z.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_487544-3_Z.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

AMPMODU_INTERCONNECTION_SYSTEM_SECTION3AND4

English

Product Specifications

Application Specification

English