TE Internal #: 5225398-1

RF Connectors, BNC RF Interface, Jack, 50 Ω , RG 58A / RG 58C /

RG 58, Snap-Fit, 4 GHz Operating Frequency, Cable-to-Panel, 1

Position, Sealable

View on TE.com >



Connectors > RF Coax Connectors > RF Connectors











RF Interface: BNC

RF Connector Style: Jack

RF Connector Mated Outer Diameter (Approximate): 14.53 mm [.572 in]

Impedance: 50Ω

Compatible With RF Cable Type: RG 58, RG 58A, RG 58B, RG 58C

Features

Product Type Features

Connector Shape	Circular
Connector Seal Type	Gasket
RF Interface	BNC
RF Connector Style	Jack
Compatible With RF Cable Type	RG 58, RG 58A, RG 58B, RG 58C
Connector System	Cable-to-Panel
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Number of Positions	1
Number of Coaxial Contacts	1
Electrical Characteristics	
Impedance	50 Ω



Gable Connector Orientation Body Material Brass Redy Plating Material Ref Connector Center Contact Underplating Material Ref Connector Center Contact Underplating Material Ref Connector Center Contact Plating Material Ref Connector Center Contact Plating Material Ref Connector Center Contact Material Ref Connector Material Ref Connector Material Ref Connector Material Ref Connector Coupling Mechanism Snap-Fit Connector Mounting Type Ref Connector Mounting Type Ref Connector Coupling Method Mechanical Detent With Dimensions Ref Connector Mated Outer Diameter (Approximate) 14.53 mm[.572 in] Usage Conditions Insulation Option Uninsulated Operating Temperature Range 65 – 165 "C[.85 – 329 "F] Operation/Application Operating Frequency 4 GHz
Contact Features RF Connector Center Contact Underplating Material Nickel 1080 µin Crimp Type Dual RF Connector Center Contact Plating Material RF Connector Center Contact Material RF Connector Center Contact Material Beryllium Copper Termination Features Termination Method to Wire & Cable Crimp Mechanical Attachment Panel Attachment Style Rear Mount RF Connector Coupling Mechanism Snap-Fit Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Uninsulated Operation/Application
RF Connector Center Contact Underplating Material 1080 μin Crimp Type Dual RF Connector Center Contact Plating Material RF Connector Center Contact Material Beryllium Copper Termination Features Termination Method to Wire & Cable Crimp Mechanical Attachment Panel Attachment Style Rear Mount RF Connector Coupling Mechanism Snap-Fit Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Uninsulated Operation/Application
Crimp Type Dual RF Connector Center Contact Plating Material Gold RF Connector Center Contact Material Beryllium Copper Termination Features Termination Method to Wire & Cable Crimp Mechanical Attachment Panel Attachment Style Rear Mount RF Connector Coupling Mechanism Snap-Fit Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) 14.53 mm[.572 in] Usage Conditions Insulation Option Uninsulated Operation/Application
Crimp Type RF Connector Center Contact Plating Material RF Connector Center Contact Material RF Connector Center Contact Material RF Connector Center Contact Material Beryllium Copper Termination Features Termination Method to Wire & Cable Crimp Mechanical Attachment Panel Attachment Panel Attachment Style Rear Mount RF Connector Coupling Mechanism Snap-Fit Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Uninsulated Operating Temperature Range -65 – 165 °C[-85 – 329 °F] Operation/Application
RF Connector Center Contact Plating Material Gold RF Connector Center Contact Material Beryllium Copper Termination Features Termination Method to Wire & Cable Crimp Mechanical Attachment Panel Attachment Panel Attachment Style Rear Mount RF Connector Coupling Mechanism Snap-Fit Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) 14.53 mm[.572 in] Usage Conditions Insulation Option Uninsulated Operating Temperature Range -65 – 165 °C[-85 – 329 °F] Operation/Application
RF Connector Center Contact Material Beryllium Copper Termination Features Termination Method to Wire & Cable Crimp Mechanical Attachment Panel Attachment Style Rear Mount RF Connector Coupling Mechanism Snap-Fit Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) 14.53 mm[.572 in] Usage Conditions Insulation Option Uninsulated Operating Temperature Range -65 – 165 °C[-85 – 329 °F] Operation/Application
Termination Features Termination Method to Wire & Cable Mechanical Attachment Panel Attachment Style Rear Mount RF Connector Coupling Mechanism Snap-Fit Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Operating Temperature Range Operation/Application
Termination Method to Wire & Cable Mechanical Attachment Panel Attachment Style Rear Mount RF Connector Coupling Mechanism Snap-Fit Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) Insulation Option Uninsulated Operating Temperature Range Operation/Application
Mechanical Attachment Panel Attachment Style Rear Mount RF Connector Coupling Mechanism Snap-Fit Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) 14.53 mm[.572 in] Usage Conditions Insulation Option Uninsulated Operating Temperature Range -65 – 165 °C[-85 – 329 °F] Operation/Application
Panel Attachment Style Rear Mount RF Connector Coupling Mechanism Snap-Fit Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) 14.53 mm[.572 in] Usage Conditions Insulation Option Uninsulated Operating Temperature Range -65 – 165 °C[-85 – 329 °F] Operation/Application
RF Connector Coupling Mechanism Connector Mounting Type Panel Mount RF Contact Captivation Method Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Uninsulated Operating Temperature Range Operation/Application
Connector Mounting Type Panel Mount RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) 14.53 mm[.572 in] Usage Conditions Insulation Option Uninsulated Operating Temperature Range -65 – 165 °C[-85 – 329 °F] Operation/Application
RF Contact Captivation Method Mechanical Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) 14.53 mm[.572 in] Usage Conditions Insulation Option Uninsulated Operating Temperature Range -65 – 165 °C[-85 – 329 °F] Operation/Application
Detent With Dimensions RF Connector Mated Outer Diameter (Approximate) 14.53 mm[.572 in] Usage Conditions Insulation Option Uninsulated Operating Temperature Range -65 – 165 °C[-85 – 329 °F] Operation/Application
Dimensions RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Uninsulated Operating Temperature Range Operation/Application Dimensions 14.53 mm[.572 in] Uninsulated -65 – 165 °C[-85 – 329 °F]
RF Connector Mated Outer Diameter (Approximate) Usage Conditions Insulation Option Uninsulated Operating Temperature Range Operation/Application 14.53 mm[.572 in] Uninsulated -65 – 165 °C[-85 – 329 °F]
Usage Conditions Insulation Option Operating Temperature Range Operation/Application Uninsulated -65 – 165 °C[-85 – 329 °F]
Insulation Option Uninsulated Operating Temperature Range -65 – 165 °C[-85 – 329 °F] Operation/Application
Operating Temperature Range -65 – 165 °C[-85 – 329 °F] Operation/Application
Operation/Application
Operating Frequency 4 GHz
Packaging Features
Packaging Method Bag
Other
Coupling Nut Base Material Brass
Grade Military
Dielectric Material PTFE

Product Compliance



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUL 2021 (219) SVHC > Threshold: Pb (3.7% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts











































Documents

CAD Files

3D PDF

English

Customer View Model ENG_CVM_5225398-1_O.2d_dxf.zip

English

Customer View Model ENG_CVM_5225398-1_O.3d_igs.zip

English

Customer View Model

RF Connectors, BNC RF Interface, Jack, 50 Ω , RG 58A / RG 58C / RG 58, Snap-Fit, 4 GHz Operating Frequency, Cable-to-Panel, 1 Position, Sealable



ENG_CVM_5225398-1_O.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

BNC Connectors

English