

5552744-7 ✓ ACTIVE

CHAMP


TE Internal #: 5552744-7

PCB D-Sub Connectors, Receptacle, Cable-to-Board, 64 Position,  
2.16 mm [.085 in] Centerline, 2 Row, Standard Profile, Right Angle,  
PCB Mount Retention

[View on TE.com >](#)



Connectors > D-Shaped Connectors > D-Sub Connectors > PCB D-Sub Connectors > D-Sub Receptacle Assembly: Right Angle, 2.16mm



Connector & Housing Type: **Receptacle**

Connector System: **Cable-to-Board**

Number of Positions: **64**

Centerline (Pitch): **2.16 mm [.085 in]**

Number of Rows: **2**

[All D-Sub Receptacle Assembly: Right Angle, 2.16mm \(21\)](#)

## Features

### Product Type Features

|                                   |                       |
|-----------------------------------|-----------------------|
| Grounded                          | No                    |
| Connector & Housing Type          | Receptacle            |
| Connector System                  | Cable-to-Board        |
| Sealable                          | No                    |
| Connector & Contact Terminates To | Printed Circuit Board |
| Shielded                          | No                    |
| Product Type                      | Connector             |
| Orientation                       | Standard              |

### Configuration Features

|                       |             |
|-----------------------|-------------|
| Number of Positions   | 64          |
| Number of Rows        | 2           |
| PCB Mount Orientation | Right Angle |
| Preloaded             | Yes         |

### Body Features

|                   |               |
|-------------------|---------------|
| Bracket Material  | Thermoplastic |
| Connector Profile | Standard      |
| Color             | Black         |



|                  |               |
|------------------|---------------|
| Plating Material | Thermoplastic |
|------------------|---------------|

### Contact Features

|   |  |
|---|--|
| Contact Mating Area Plating Material          | Gold or Gold Flash over Palladium Nickel |
| Contact Underplating Material                 | Palladium Nickel                         |
| PCB Contact Termination Area Plating Material | Tin                                      |
| Contact Base Material                         | Copper Alloy                             |
| Contact Current Rating (Max)                  | 1 A                                      |
|   | 30 $\mu$ m                               |

### Termination Features

|   |                       |
|---|-----------------------|
| Termination Method to Printed Circuit Board | Through Hole - Solder |
|---|-----------------------|

### Mechanical Attachment

|                          |                           |
|--------------------------|---------------------------|
| Panel Attachment Style   | Rear Mount                |
| Panel Mount Feature      | With                      |
| PCB Mount Retention      | With                      |
| PCB Mount Retention Type | Self-Tapping              |
| Mating Retention         | With                      |
| Mating Retention Type    | Threaded Insert, 4-40 UNC |
| Connector Mounting Type  | Board Mount               |

### Housing Features

|                    |                   |
|--------------------|-------------------|
| Centerline (Pitch) | 2.16 mm [.085 in] |
| Housing Material   | Thermoplastic     |
| Housing Color      | Black             |

### Dimensions

|                    |                   |
|--------------------|-------------------|
| Row-to-Row Spacing | 4.3 mm [.169 in]  |
| Panel Thickness    | 1.57 mm [.062 in] |
| PCB Tail Length    | 2.54 mm [.1 in]   |

### Usage Conditions

|                             |                             |
|-----------------------------|-----------------------------|
| Operating Temperature Range | -55 – 105 °C [-67 – 221 °F] |
|-----------------------------|-----------------------------|

### Operation/Application

|                     |        |
|---------------------|--------|
| Circuit Application | Signal |
|---------------------|--------|

### Industry Standards

|                        |          |
|------------------------|----------|
| UL Flammability Rating | UL 94V-0 |
|------------------------|----------|



### Packaging Features

|                    |      |
|--------------------|------|
| Packaging Method   | Tray |
| Packaging Quantity | 30   |

### Other

|               |               |
|---------------|---------------|
| Comb Material | Thermoplastic |
|---------------|---------------|

### Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)

|   |  |
|---|--|
| EU RoHS Directive 2011/65/EU                  | Compliant with Exemptions  |
| EU ELV Directive 2000/53/EC                   | Compliant with Exemptions  |
| China RoHS 2 Directive MIIT Order No 32, 2016 | Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2022 (224)<br>Candidate List Declared Against: JAN 2020 (205)<br>SVHC > Threshold:<br>Not Yet Reviewed |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.   |
| Solder Process Capability                     | Wave solder capable to 265°C   |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

### Compatible Parts



## Documents

### Product Drawings

[ASSY,RCPT,64 POSN,RTANG,PCB](#)

English

### CAD Files

Customer View Model

[ENG\\_CVM\\_CVM\\_5552744-7\\_B.2d\\_dxf.zip](#)

English

3D PDF

3D

Customer View Model

[ENG\\_CVM\\_CVM\\_5552744-7\\_B.3d\\_igs.zip](#)

English

Customer View Model

[ENG\\_CVM\\_CVM\\_5552744-7\\_B.3d\\_stp.zip](#)

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

### Product Specifications

[Application Specification](#)

English