

CII

TE Internal #: 5-1617076-2 1/5-Size Relays, 4 Form C, 4PDT, 4 C/O, 26.5 VDC Input, Coil Suppression Diode, 2 A, 26.5 VDC Coil Voltage, 720 Ω Coil Resistance

View on TE.com >

Relays, Contactors & Switches > Relays > Mil-Aero Relays > 1/5-Size Relays



- 1/5-Size Relay Contact Arrangement: 4 Form C, 4PDT, 4 C/O
- 1/5-Size Relay Input Voltage: 26.5 VDC
- Coil Suppression Diode: With
- 1/5-Size Relay Contact Current Rating: 2A
- 1/5-Size Relay Coil Voltage Rating: 26.5 VDC

Features

Product Type Features

Enclosure Type

Relay Type

Hermetically Sealed

Military/Aerospace High Performance

\ \ / . . |



Without
Relay
Without
Without
DC
30G's, 10–3000Hz
Non-Polarized, Monostable
100G's, 11ms
Milliwatts
Without
26.5 VDC
With
26.5 VDC

3SBH5134K5

1/5-Size Relays, 4 Form C, 4PDT, 4 C/O, 26.5 VDC Input, Coil Suppression Diode, 2 A, 26.5 VDC Coil Voltage, 720 Ω Coil Resistance



1/5-Size Relay Coil Resistance	720 Ω
1/5-Size Relay Coil Power Rating (DC)	975 mW
Contact Features	
1/5-Size Relay Contact Arrangement	4 Form C, 4PDT, 4 C/O
1/5-Size Relay Contact Current Rating	2 A
Termination Features	
Termination Type	PC Pins
Mechanical Attachment	
1/5-Size Relay Mounting Type	Chassis Mount
Usage Conditions	
Operating Temperature Range	-65 – 125 °C
Product Compliance	
For compliance documentation, visit the product page on TE.com>	

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold

Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed

Halogen Content

Not Yet Reviewed for halogen content

Solder Process Capability

Not lead free process capable

Product Compliance Disclaimer

EU REACH Regulation (EC) No. 1907/2006

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the

3SBH5134K5

1/5-Size Relays, 4 Form C, 4PDT, 4 C/O, 26.5 VDC Input, Coil Suppression Diode, 2 A, 26.5 VDC Coil Voltage, 720 Ω Coil Resistance



product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-1617076-2_E.2d_dxf.zip

English

Customer View Model ENG_CVM_CVM_5-1617076-2_E.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_5-1617076-2_E.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 5-1773450-5_sec1_3SBH

English

RELAY

English