

### **AMPLIVAR**

TE Internal #: 62295-2

Splices, 12 – 10 AWG Wire Size, 3.46 – 6 mm² Wire Size, Splice

Capacity 3, 7000 – 12000 CMA Wire Size, Brass, Pigtail Splice

Splice, AMPLIVAR


View on TE.com >



Terminals & Splices > Splices











Wire Size: 7000 – 12000 CMA

Sealable: No

Splice Capacity: 3

### **Features**

### **Product Type Features**

Sealable	No
Splice Type	Pigtail Splice
Serrated	Yes
Compatible With Discrete Wire Type	Magnet Wire, Solid
Configuration Features	

Strip Orientation	End Feed
Splice Capacity	3
Number of Serrations	7

### **Electrical Characteristics**

### **Body Features**

Weight per Piece	.302 g
Plating Material	Unplated
Primary Product Material	Brass

### **Contact Features**



Contact Plating Material	Unplated
Barrel Type	Open
Termination Features	
Crimp Width	6.35 mm[.25 in]
Mechanical Attachment	
Wire Insulation Support	Without
Dimensions	
Wire Size	7000 – 12000 CMA
Terminal Material Thickness	.64 mm[.025 in]
Overall Product Length	5.72 mm[.225 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-65 – 150 °C[-85 – 302 °F]
Operation/Application	
Heavy Duty	No
Compatible With Wire Base Material	Copper
Industry Standards	
Government Qualified Splice	No
Packaging Features	
Packaging Quantity	12500
Packaging Method	Strip

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC



#### Free

### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**





## Also in the Series | AMPLIVAR







Magnet Wire Terminals(5)



PCB Terminals(1)



Quick Disconnects(42)



Ring Terminals & Spade Terminals(28)



**Documents** 



### **Product Drawings**

AMVAR SPLC 7000-12000 025BR

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_62295-2\_L\_c-62295-2-l.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_62295-2\_L\_c-62295-2-l.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_62295-2\_L\_c-62295-2-l.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### Datasheets & Catalog Pages

Magnet Wire Terminals & Splices

English

**Product Specifications** 

**Application Specification** 

English

AMPLIVAR 7 Serration Pigtail Splice

English