

### Positive Lock | Positive Lock 250

TE Internal #: 63119-1

Quick Disconnects, Receptacle, 22 – 18 AWG Wire Size, .32 – .82 mm<sup>2</sup> Wire Size, Mating Tab Width .25 in [6.35 mm], Straight, Brass,

Positive Lock 250

View on TE.com >



Terminals & Splices > Quick Disconnects











Quick Disconnect Terminal Type: Receptacle

Wire Size: .32 – .82 mm<sup>2</sup>

Mating Tab Width: 6.35 mm [.25 in]

Mating Tab Thickness: .81 mm [.032 in]

## **Features**

## **Product Type Features**

| Terminates To   | Wire & Cable |
|-----------------|--------------|
| Wire Stop       | No           |
| Wire/Cable Type | Regular Wire |
| Insertion Force | Low          |
| Sealable        | No           |

## **Configuration Features**

| Connection Capacity | Single |
|---------------------|--------|
|---------------------|--------|

## **Contact Features**

| Quick Disconnect Terminal Type | Receptacle      |
|--------------------------------|-----------------|
| Mating Tab Width               | 6.35 mm[.25 in] |
| Mating Tab Thickness           | .81 mm[.032 in] |
| Terminal Orientation           | Straight        |
| Contact Base Material          | Brass           |
| Terminal Plating Material      | Tin             |
| Crimp Type                     | F-Crimp         |



| Barrel Type                            | Open                        |
|--|-----------------------------|
| Mechanical Attachment                  |                             |
| Mating Retention Type                  | Dimple                      |
| Wire Insulation Support                | With                        |
| Dimensions                             |                             |
| Accepts Wire Insulation Diameter Range | 1.52 – 2.54 mm[.06 – .1 in] |
| Overall Length                         | 22.5 mm[.886 in]            |
| Receptacle Terminal Stock Thickness    | .41 mm[.016 in]             |
| Wire Size                              | $.3282 \text{ mm}^2$        |
| Usage Conditions                       |                             |
| Insulation Option                      | Uninsulated                 |
| Operating Temperature Range            | -40 - 110 °C[-40 - 230 °F]  |
| Industry Standards                     |                             |
| UL Rating                              | Recognized                  |
| Packaging Features                     |                             |
| Packaging Quantity                     | 6000                        |
|  |                             |

# **Product Compliance**

Packaging Method

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC |
| Halogen Content                               | Low Halogen - Br, Cl, F, I < 900 ppm per<br>homogenous material. Also BFR/CFR/PVC<br>Free                                 |
| Solder Process Capability                     | Not applicable for solder process capability  |
|   |   |

Strip/Reel

Product Compliance Disclaimer



This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

# **Compatible Parts**



TE Part # 2-2150297-2 OCEAN\_2.0\_Applicator-E-090F140F



TE Part # 2150297-2 OCEAN\_2.0\_Applicator-E-090F140F



HSG,RECP,POSI-LOCK&STD FAST250



TE Part # 7-2150297-2 OCEAN\_2.0\_Applicator-E-090F140F



# Also in the Series | Positive Lock 250



Automotive Terminals(1)



Crimp Terminal Housings(202)




Insertion & Extraction Tools(3)



Insulation Boots & Sleeves(4)





#### **Documents**

#### **Product Drawings**

POSITIVE LOCK 250 REC 22-18 AWG TPBR

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_63119-1\_AP.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_63119-1\_AP.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_63119-1\_AP.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

Positive Lock Receptacles

English

## **Product Specifications**

**Application Specification** 

English

## **Product Environmental Compliance**

TE Material Declaration

English