MAG-MATE

TE Internal #: 63551-3

Magnet Wire Terminals, Poke-In, Size 2, .51 – .64 mm Aluminum

Wire, 24 – 22 AWG Aluminum Wire, 27 – 23 AWG Magnet Wire,

MAG-MATE

View on TE.com >



Terminals & Splices > Magnet Wire Terminals











Magnet Wire Terminal Type: Poke-In
Compatible With Cavity Size: Size 2
Aluminum Wire Size: .51 – .64 mm
Magnet Wire Size: 27 – 23 AWG

Features

Product Type Features	
Compatible With Discrete Wire Type	Magnet Wire, Solid
Sealable	No
Body Features	
Compatible With Cavity Size	Size 2
Contact Features	
Magnet Wire Terminal Type	Poke-In
Terminal Plating Material	Tin
Contact Underplating Material	Nickel
Terminal Orientation	Twisted
Termination Features	
Termination Method to Wire & Cable	Insulation Displacement (IDC)
Dimensions	
Terminal Height	7.62 mm[.3 in]

.51 – .64 mm

Aluminum Wire Size



Magnet Wire Size	.36 – .57 mm
Stock Thickness (Magnet Wire Side)	.41 mm[.016 in]
Overall Product Length	7.87 mm[.309 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-65 – 150 °C[-85 – 302 °F]
Operation/Application	
Compatible With Wire Base Material	Aluminum, Copper
Identification Marking	
Identification Number	10
Packaging Features	
Packaging Quantity	12000
Packaging Method	Reel, Reel/Carton
Other	
Comment	Two magnet wires may be terminated in the same terminal slot if diameters are equal.

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent



chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts










Also in the Series | MAG-MATE







Magnet Wire Terminals(462)



PCB Terminals(1)

Documents

Product Drawings

MAG-MATE LEAF CONT 016 TPPHBZ

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_63551-3_Z.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_63551-3_Z.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_63551-3_Z.3d_stp.zip

Magnet Wire Terminals, Poke-In, Size 2, .51 – .64 mm Aluminum Wire, 24 – 22 AWG Aluminum Wire, 27 – 23 AWG Magnet Wire, MAG-MATE



English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Magnet Wire Terminals & Splices

English

Product Specifications

Application Specification

English