
3SBC1623A2

CII

TE Internal #: 7-1617347-5 1/5-Size Relays, 2 Form C, DPDT, 2 C/O, 26.5 VDC Input, Coil Suppression Diode, 2 A, 26.5 VDC Coil Voltage, 1350 Ω Coil Resistance

View on TE.com >

Relays, Contactors & Switches > Relays > Mil-Aero Relays > 1/5-Size Relays



1/5-Size Relay Contact Arrangement: **2 Form C, DPDT, 2 C/O**

1/5-Size Relay Input Voltage: 26.5 VDC

Coil Suppression Diode: With

1/5-Size Relay Contact Current Rating: 2A

1/5-Size Relay Coil Voltage Rating: 26.5 VDC

Features

Product Type Features

Enclosure Type

Relay Type

Hermetically Sealed

Military/Aerospace High Performance

\ \ / . . |



Product TypeRelayMOSFET DriverWithoutConfiguration FeaturesWithoutTransistor DriverWithoutEctrical CharacteristicsDCVibrationDCVibration30G's, 10 – 3000HzCoil Magnetic SystemNon-Polarized, MonostableShock75 G's, 6msCoil Power MeasurementMilliwattsCoil Polarity Protection DiodeWithout1/5-Size Relay Input Voltage6.5 VDCI/5-Size Relay Coil Voltage Rating26.5 VDC	Coil Latching	Without
Configuration Features Transistor Driver Without Electrical Characteristics Actuating System DC Actuation System DC Vibration 30G's, 10 – 3000Hz Coil Magnetic System Non-Polarized, Monostable Shock 75 G's, 6ms Coil Power Measurement Without I Oplarity Protection Diode Without 1/5-Size Relay Input Voltage 26.5 VDC Coil Suppression Diode Without	Product Type	Relay
Transistor DriverWithoutFlectrical CharacteristicsDCActuating SystemDCVibration30G's, 10 – 3000HzCoil Magnetic SystemNon-Polarized, MonostableShock75 G's, 6msCoil Power MeasurementMilliwattsCoil Polarity Protection DiodeWithout1/5-Size Relay Input Voltage26.5 VDCCoil Suppression DiodeWithout	MOSFET Driver	Without
Fectrical Characteristics Actuating System DC Vibration 30G's, 10 – 3000Hz Coil Magnetic System Non-Polarized, Monostable Shock 75 G's, 6ms Coil Power Measurement Milliwatts Coil Polarity Protection Diode Without 1/5-Size Relay Input Voltage 26.5 VDC Coil Suppression Diode Without	Configuration Features	
Actuating SystemDCVibration30G's, 10 – 3000HzCoil Magnetic SystemNon-Polarized, MonostableShock75 G's, 6msCoil Power MeasurementMilliwattsCoil Polarity Protection DiodeWithout1/5-Size Relay Input Voltage26.5 VDCCoil Suppression DiodeWith	Transistor Driver	Without
Vibration30G's, 10 – 3000HzCoil Magnetic SystemNon-Polarized, MonostableShock75 G's, 6msCoil Power MeasurementMilliwattsCoil Polarity Protection DiodeWithout1/5-Size Relay Input Voltage26.5 VDCCoil Suppression DiodeWith	Electrical Characteristics	
Coil Magnetic SystemNon-Polarized, MonostableShock75 G's, 6msCoil Power MeasurementMilliwattsCoil Polarity Protection DiodeWithout1/5-Size Relay Input Voltage26.5 VDCCoil Suppression DiodeWith	Actuating System	DC
Shock75 G's, 6msCoil Power MeasurementMilliwattsCoil Polarity Protection DiodeWithout1/5-Size Relay Input Voltage26.5 VDCCoil Suppression DiodeWith	Vibration	30G's, 10–3000Hz
Coil Power MeasurementMilliwattsCoil Polarity Protection DiodeWithout1/5-Size Relay Input Voltage26.5 VDCCoil Suppression DiodeWith	Coil Magnetic System	Non-Polarized, Monostable
Coil Polarity Protection DiodeWithout1/5-Size Relay Input Voltage26.5 VDCCoil Suppression DiodeWith	Shock	75 G's, 6ms
1/5-Size Relay Input Voltage26.5 VDCCoil Suppression DiodeWith	Coil Power Measurement	Milliwatts
Coil Suppression Diode With	Coil Polarity Protection Diode	Without
	1/5-Size Relay Input Voltage	26.5 VDC
1/5-Size Relay Coil Voltage Rating 26.5 VDC	Coil Suppression Diode	With
	1/5-Size Relay Coil Voltage Rating	26.5 VDC

3SBC1623A2

1/5-Size Relays, 2 Form C, DPDT, 2 C/O, 26.5 VDC Input, Coil Suppression Diode, 2 A, 26.5 VDC Coil Voltage, 1350 Ω Coil Resistance



1/5-Size Relay Coil Resistance	1350 Ω
1/5-Size Relay Coil Power Rating (DC)	520 mW
Contact Features	
1/5-Size Relay Contact Arrangement	2 Form C, DPDT, 2 C/O
1/5-Size Relay Contact Current Rating	2 A
Termination Features	
Termination Type	Solder Hook Terminal
Mechanical Attachment	
1/5-Size Relay Mounting Type	Panel Mount
Usage Conditions	
Operating Temperature Range	-65 – 125 °C
Product Compliance	
For compliance documentation, visit the product page on TE.com>	

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold

Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed

Halogen Content

Not Yet Reviewed for halogen content

Solder Process Capability

Not lead free process capable

Product Compliance Disclaimer

EU REACH Regulation (EC) No. 1907/2006

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the

3SBC1623A2

1/5-Size Relays, 2 Form C, DPDT, 2 C/O, 26.5 VDC Input, Coil Suppression Diode, 2 A, 26.5 VDC Coil Voltage, 1350 Ω Coil Resistance



product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

Compatible Parts



TE Part # 1-1617076-3 3SBH1142A2 = M39016/14-002L

Documents

Product Drawings 3SBC1623A2=M39016/37-023L

English

Datasheets & Catalog Pages 5-1773450-5_sec1_3SBC

English