

## RAST | RAST 5 IDC Connectors

TE Internal #: 8-928344-2


Housing, Receptacle, Wire-to-Board, 2 Position, 5 mm [.197 in] Centerline, Crimp, 1 Row, Violet, Mating Retention, Wire & Cable,

RAST 5 IDC Connectors

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings











Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board

Number of Positions: 2

Centerline (Pitch): 5 mm [.197 in]

## **Features**

## **Product Type Features**

Connector Product Type	Housing
Connector & Housing Type	Receptacle
Connector System	Wire-to-Board
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Configuration Features	
Keying & Polarized Rib Location	1b/2b
Number of Positions	2
Number of Rows	1
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Locking Latch Between Cavity Number	1&2

Without

Strain Relief



Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Latch
Mating Retention	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PA 6.6
Centerline (Pitch)	5 mm[.197 in]
Housing Color	Violet
Dimensions	
Connector Length	10 mm[.39 in]
	400 [40:]
Connector Height	12.2 mm[.48 in]
Usage Conditions	12.2 mm[.48 in]
	-40 - 105 °C[-40 - 221 °F]
Usage Conditions	
Usage Conditions  Operating Temperature Range	
Usage Conditions  Operating Temperature Range  Operation/Application	-40 – 105 °C[-40 – 221 °F]
Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application	-40 – 105 °C[-40 – 221 °F]
Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards	-40 – 105 °C[-40 – 221 °F]  Power
Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards  RAST Version	-40 – 105 °C[-40 – 221 °F]  Power  02-B
Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards  RAST Version  Glow Wire Rating	-40 – 105 °C[-40 – 221 °F]  Power  02-B  Standard Part - Not Glow Wire
Usage Conditions  Operating Temperature Range  Operation/Application  Circuit Application  Industry Standards  RAST Version  Glow Wire Rating  UL Flammability Rating	-40 – 105 °C[-40 – 221 °F]  Power  02-B  Standard Part - Not Glow Wire

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUNE 2022 (224)



Does no	t contain	RFACH	SVHC
D062 110	t Contain	NL A C H	$\mathcal{I}$

Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

### Solder Process Capability

Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

# Compatible Parts



























# Also in the Series | RAST 5 IDC Connectors








Connector Contacts(12)



Crimp Terminal Housings(41)



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(424)



Rectangular Connector Housings(1)



Standard Edge Connectors(47)



Standard Rectangular Connectors(112)



Wire-to-Board Connector Assemblies & Housings(213)



Wire-to-Board Connector Contacts(2)

## **Documents**

**Product Drawings** 

STD-TIMER GEH 2P

English

### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_8-928344-2\_B.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_8-928344-2\_B.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_8-928344-2\_B.3d\_stp.zip

English

Housing, Receptacle, Wire-to-Board, 2 Position, 5 mm [.197 in] Centerline, Crimp, 1 Row, Violet, Mating Retention, Wire & Cable, RAST 5 IDC Connectors



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Agency Approvals

**VDE Certificate** 

English