


TE Internal #: 966144-1

Crimp Wire Pins, Tabs & Ferrules, Ferrule, 20 AWG Wire Size, .5 mm<sup>2</sup> Wire Size, 1022 CMA Wire Size, Closed, Tin Plating, Length 15 mm [.591 in], Bag

View on TE.com >



Terminals & Splices > Crimp Wire Pins, Tabs & Ferrules



Crimp Wire Pin, Tab & Ferrule Terminal Type: Ferrule

Accepts Wire Insulation Diameter Range: 2.25 mm [ .08 in ]

Wire Size: 1022 CMA

# **Features**

# **Product Type Features**

Sealable	No
Compatible With Discrete Wire Type	Stranded
Configuration Features	
Compatible With Wire & Cable Type	Discrete Wire
Body Features	
Double Wire	Yes
Contact Features	
Terminal Length	8 mm[.312 in]
Crimp Wire Pin, Tab & Ferrule Terminal Type	Ferrule
Barrel Type	Closed
Terminal Plating Material	Tin
Terminal Orientation	Straight
Mechanical Attachment	
Wire Insulation Support	Without

**Dimensions** 



2-Wire Size	20 AWG
Strip Length	11 mm[.433 in]
Accepts Wire Insulation Diameter Range	2.25 mm[.08 in]
Wire Size	1022 CMA
Terminal Material Thickness	.15 mm[.005 in]
Overall Product Length	15 mm[.591 in]
Usage Conditions	
Insulation Option	Partially Insulated
Operating Temperature Range	105 °C[221 °F]
Operation/Application	
Heavy Duty	No
Packaging Features	
Packaging Quantity	500

Bag

White

# **Product Compliance**

Packaging Method

Barrel Color

Other

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these



limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





## **Documents**

### **Product Drawings**

DOPPLEIT ADERENDH N

English

## **CAD Files**

3D PDF

English

**Customer View Model** 

ENG\_CVM\_966144-1\_B2.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_966144-1\_B2.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_966144-1\_B2.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# **Datasheets & Catalog Pages**

**BUCHANAN TERMINAL BLOCKS CATALOG - EUROSTYLE TERMINAL BLOCKS** 

English

Wire Ferrules

English

WIRE END FERRULES

English

#### **Agency Approvals**

Crimp Wire Pins, Tabs & Ferrules, Ferrule, 20 AWG Wire Size, .5 mm² Wire Size, 1022 CMA Wire Size, Closed, Tin Plating, Length 15 mm [.591 in], Bag



# **CSA Certificate**

English