
ZHD-SCE-4.8-50-4 - ACTIVE

RAYCHEM | ZHD-SCE

TE Internal #: EC9834-000 Printable Tubing, Ladder, Low Fire Hazard, 2:1 Shrink Ratio, Yellow, Markers per Sleeve 1, Length 2 in [50 mm], 2.36 mm [.09 in] Recovered Inside

View on TE.com >





Printable Tubing Type: Ladder
Printable Tubing Grade: Low Fire Hazard
Printable Tubing Shrink Ratio: 2:1
Primary Product Color: Yellow
Markers per Sleeve: 1

All Fluid Resistant Sleeves, ZHD-SCE (88)

Features

Product Type Features

Printable Tubing Type



Ladder

Printable Tu	bing Grade
--------------	------------

Low Fire Hazard

Body Features

Printable Tubing Shrink Ratio	2:1
Primary Product Color	Yellow
Markers per Sleeve	1
Dimensions	
Product Length	50 mm[2 in]
Supplied Inner Diameter	4.8 mm[.189 in]
Recovered Inside Diameter	2.36 mm[.09 in]
Compatible Cable Diameter Range	2.54 – 4.06 mm[.1 – .16 in]
Usage Conditions	
Operating Temperature Range	-55 – 125 °C[-67 – 257 °F]
Operation/Application	
Recommended Ribbon	See TE Document 411-121005 the Printer Product Ribbon Matrix

ZHD-SCE-4.8-50-4

Printable Tubing, Ladder, Low Fire Hazard, 2:1 Shrink Ratio, Yellow, Markers per Sleeve 1, Length 2 in [50 mm], 2.36 mm [.09 in] Recovered Inside



Printer/Label Features

Recommended Printer	See TE Document 411-121005 the Printer Product Ribbon Matrix
Printer Technology	Thermal Transfer
Packaging Features	
Packaging Quantity	250
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts

ZHD-SCE-4.8-50-4

Printable Tubing, Ladder, Low Fire Hazard, 2:1 Shrink Ratio, Yellow, Markers per Sleeve 1, Length 2 in [50 mm], 2.36 mm [.09 in] Recovered Inside







Also in the Series ZHD-SCE



Documents

Product Drawings ZHD-SCE-4.8-50-4

English

Datasheets & Catalog Pages TTDS for ZHD-SCE, LOW FIRE HAZARD, DIESEL RESISTANT

English

Product Specifications

Product Specification

English

IDENTIFCATION PRINTER PRODUCT RIBBON MATRIX

English

Instruction Sheets

Instruction Sheet (non U.S.)

English

ZHD-SCE-4.8-50-4

Printable Tubing, Ladder, Low Fire Hazard, 2:1 Shrink Ratio, Yellow, Markers per Sleeve 1, Length 2 in [50 mm], 2.36 mm [.09 in] Recovered Inside

