# ZHD-SCE-1K-19.0-50-4 - ACTIVE

#### **ZHD-SCE**

TE Internal #: EC9860-000 Printable Tubing, Ladder, Fluid Resistant & Low Fire Hazard, 2:1 Shrink Ratio, Yellow, Markers per Sleeve 1, Length 2 in [50 mm], ZHD-SCE

View on TE.com >



Identification & Labeling > Printable Tubing > Fluid Resistant Sleeves, ZHD-SCE



Printable Tubing Type: Ladder
Printable Tubing Grade: Fluid Resistant & Low Fire Hazard
Printable Tubing Shrink Ratio: 2:1
Primary Product Color: Yellow
Markers per Sleeve: 1

All Fluid Resistant Sleeves, ZHD-SCE (88)

#### Features

#### Product Type Features

Printable Tubing Type

Ladder

Printable Tubing Grade

Fluid Resistant & Low Fire Hazard

#### **Body Features**

Printable Tubing Shrink Ratio	2:1
Primary Product Color	Yellow
Markers per Sleeve	1
Dimensions	
Product Length	50 mm[2 in]
Supplied Inner Diameter	19 mm[.73 in]
Recovered Inside Diameter	9.5 mm[.375 in]
Compatible Cable Diameter Range	10.1 – 16.2 mm[.4 – .64 in]
Usage Conditions	
Operating Temperature Range	-55 – 135 °C[-67 – 275 °F]
Operation/Application	
Recommended Ribbon	See TE Document 411-121005 the Printer Product Ribbon Matrix

**C** For support call+1 800 522 6752

11/01/2022 08:34AM | Page 1

#### ZHD-SCE-1K-19.0-50-4

Printable Tubing, Ladder, Fluid Resistant & Low Fire Hazard, 2:1 Shrink Ratio, Yellow, Markers per Sleeve 1, Length 2 in [50 mm], ZHD-SCE



#### Printer/Label Features

Recommended Printer	See TE Document 411-121005 the Printer Product Ribbon Matrix
Printer Technology	Thermal Transfer
Packaging Features	
Packaging Quantity	1000
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2022 (224) Candidate List Declared Against: JUL 2021 (219) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

### **Compatible Parts**

#### ZHD-SCE-1K-19.0-50-4

Printable Tubing, Ladder, Fluid Resistant & Low Fire Hazard, 2:1 Shrink Ratio, Yellow, Markers per Sleeve 1, Length 2 in [50 mm], ZHD-SCE







## Also in the Series **ZHD-SCE**



### Documents

**Product Drawings** ZHD-SCE-1K-19.0-50-4

English

#### Datasheets & Catalog Pages **IDENTIFICATION SELECTION GUIDE**

English

#### TTDS for ZHD-SCE, LOW FIRE HAZARD, DIESEL RESISTANT

English

#### **Product Specifications**

**Product Specification** 

English

#### IDENTIFCATION PRINTER PRODUCT RIBBON MATRIX

English

#### **Instruction Sheets**

**C** For support call+1 800 522 6752

#### ZHD-SCE-1K-19.0-50-4

Printable Tubing, Ladder, Fluid Resistant & Low Fire Hazard, 2:1 Shrink Ratio, Yellow, Markers per Sleeve 1, Length 2 in [50 mm], ZHD-SCE



Instruction Sheet (non U.S.)

English