

A WORD FROM DAN ARIENS

= continuing the legend

For many of us, those hours of digging into a landscape project is a refreshing escape from your cell phone, email and the weekly grind. Whether you're mowing a large yard or touching up a small edge, you should expect your lawn equipment investment not to interrupt those few precious hours of "Your Time."

The smell of fresh cut grass on a summer afternoon. The pride in a beautiful yard. The satisfaction of a job well-done. Our family pride comes from knowing we can assure you these important pleasures of life.

When you choose an Ariens product you become family and part of our rich 80-year family heritage. When my great-grandfather Henry Ariens started building equipment in 1933, he built durable products designed to be reliable year after year – generation after generation. Today we continue to

live by the standards that my grandfather set when he began the Ariens Company.

Our company vision is simple. Passionate People, Astounded Customers. You can rest assured that Ariens continues to manufacture products with the same drive for quality and respect for our customers that began in the early days. We do this with a single goal in mind – so you can pass the power of our equipment on to your next generation.

Welcome to the family!

Dan AriensPresident & CEO



TABLE OF CONTENTS

HIGH PERFORMANCE LANDSCAPE SOLUTION

Quality components and robust construction are essential to achieving a pristine, flawless landscape. Whether the challenge is a sprawling estate with acres of property, family cottage with decorative surfaces and rustic wood burning fireplace, Ariens Company is proud to provide an exceptional lineup of landscape solutions engineered to make your home beautiful for generations.













PASSIONATELY OVER-BUILT IN

BRILLION, USA

Exceptional durability. Reliable performance. Unsurpassed results. Backed by industry-leading warranties, Ariens Lawn & Garden lineup offers a wide range of landscape solutions engineered to suit the diverse needs of today's consumers.





Every piece of Ariens equipment is engineered to be rugged and reliable with emphasis on the highest American Craftsmanship standards to ensure years of legendary performance.



Unsurpassed design. Unrivaled guarantees. Every Ariens product comes backed by a 3-year warranty supported by an extensive independent dealer network.

THE FAMILY STORY

HERITAGE & INNOVATION

Over 80 years ago, a spark flew and a legend was born when Henry Ariens alongside his three sons — Steve, Leon, and Francis — created the first American-made rotary tiller. At a time when others experimented with foreign equipment, they stood at the forefront of innovation determined to innovate exceptional solutions to overcome the agricultural challenges of their era. Through years of hard-work, education, and perseverance, Henry and his sons revolutionized agriculture across the Country by providing exceptional, long-lasting products that empowered commercial growers like never before.

Today, Ariens Company proudly carries on a rich legacy grounded by American craftsmanship while fusing it with leading designs and manufacturing capabilities you can depend on generation after generation. Designed, fabricated, and assembled under world-class Lean manufacturing principles, Ariens products feature only the best quality components from thick, all-steel frames to robust engine options. At the core of the Ariens Company vision is a quest to astound its customers which is why every product is passionately overbuilt to provide unsurpassed results and longevity. For outdoor equipment to make your yard beautiful, the solution is simple — turn to Ariens, a heritage of American craftsmanship and innovation trusted for over 80 years – turn to the Ariens family.



MAX ZOOM® SERIES Engineered with excellence. Manufactured for yo

Available with a 48", 52", or 60" deck size, the Ariens Max Zoom series is ideal for homeowners looking to overcome the challenges of large yards and varying landscapes. Features include robust components, Hydo-Gear® transaxles, and a fabricated 4-point commercial deck for long-life and a flawless finish in a fraction of the time it takes with other mowers. Supported by a 3-year limited consumer warranty and a 5-year deck shell and frame warranty, the Ariens Max Zoom is an exceptional value manufactured to provide years of reliable performance.



MODEL OVERVIEW:

Max Zoom®	Model #	Kohler® 7000 Twin	Kohler® 7000 Pro Twin	Cutting Width	Ground Speed (Fwd/Rev)	Fuel Capacity
Max Zoom® 60	991087	•	25 HP/ 725 CC	60"	8 MPH/4 MPH	6.0 GAL. / 22.7 L
Max Zoom® 52	991086	23 HP/ 725 CC	•	52"	8 MPH/4 MPH	6.0 GAL. / 22.7 L
Max Zoom® 48	991085	22 HP/ 725 CC	•	48"	8 MPH/4 MPH	6.0 GAL. / 22.7 L



as professional mowers.





ZOOM® XL SERIES A legacy of quality craftsmanship you can trust.

Complete with your choice of a 42", 48", or 54" fully fabricated and welded deck, the Ariens Zoom XL tackles medium to large yards with ease and efficiency. A foot-operated deck lift makes it easy to adjust the cutting height from 1.5" to 4.5" in 1/2" increments to ensure the manicured landscape you strive for. Best of all, dependable performance is what you can expect with a Kohler 7000 series twin cylinder, OHV engine as the driving force behind this zero-turn.



MODEL OVERVIEW:

Zoom® XL	Model #	Kohler® 7000 Twin	Cutting Width	Ground Speed (Fwd/Rev)	Fuel Capacity
Zoom® XL 54	915173	24 HP/ 725 CC	54"	6.5 MPH/3 MPH	3.8 GAL. / 14.4 L
Zoom® XL 48	915165	22 HP/ 725 CC	48"	6.5 MPH/3 MPH	3.8 GAL. / 14.4 L
Zoom® XL 42	915163	20 HP/ 725 CC	42"	6.5 MPH/3 MPH	3.8 GAL. / 14.4 L



10-Gauge Fabricated Deck delivers an excellent cut quality along with a level of durability typically found in commercial mowers.

Hydro-Gear[®] **ZT-2800 Series Transaxles** create a smooth driving experience.

Foot-Operated Deck Lift allows the user to adjust the height of cut from 1.5" to 4.5" in $\frac{1}{2}$ " increments with a simple lever.

Approximate maximum speed of 6.5 mph forward and 3 mph reverse.

Kohler® **7000 Series** twin cylinder, OHV engine provides perfectly matched power and performance with 20 to 24 hp.







ZOOM® SERIES Designed and built to last generations.

Engineered for performance yet designed to suit the versatile needs of today's homeowner, the Ariens Zoom Series mower is ideal for small to mid sized lawns. Choose between a 34", 42", or 50" deck to meet your landscaping needs and preferences. Enjoy an unmatched level of operator comfort and user-friendly controls which reduce operator fatigue. Complete with robust components including a 12-gauge stamped XLerator™ deck and a foot-operated deck lift, this mower is designed to last for many years.





LAWN TRACTORS Ride your way to a flawless finish.

When it comes to investing in a lawn tractor, the last thing you should do is settle. Equip yourself with the power and reliable performance of an Ariens lawn tractor to achieve the landscape you long for. Built with American craftsmanship and durable components, Ariens lawn tractors are easy to operate and comfortable to use for complete operator satisfaction long into the future.



Tractors	Model #	Kohler® Courage Single	Kohler® 7000 Twin	Drive	Cutting Width	Turning Radius	Ground Speed (Fwd/Rev)	Fuel Capacity
Garden Tractor 54	936096	•	25 HP/725 CC	Hydro Foot Pedal	54"	10"	5.5 MPH/2.5 MPH	4 GAL. / 15.2 L
Lawn Tractor 54	936097	•	25 HP/725 CC	Hydro Foot Pedal	54"	10"	5.5 MPH/2.5 MPH	3 GAL. / 11.4 L
Lawn Tractor 48	936098	•	22 HP/725 CC	Hydro Foot Pedal	48"	10"	5.5 MPH/2.5 MPH	3 GAL. / 11.4 L
Lawn Tractor 46	936099	•	22 HP/725 CC	Hydro Foot Pedal	46"	10"	5.5 MPH/2.5 MPH	2.5 GAL. / 9.5 L
Lawn Tractor 20/42	936100	20 HP/597 CC	•	Hydro Foot Pedal	42"	10"	5.5 MPH/2.5 MPH	2.5 GAL. / 9.5 L
Lawn Tractor 17/42	936101	17 HP/597 CC	•	6 Speed Gear Drive	42"	16"	5.5 MPH/2.5 MPH	1.5 GAL. / 5.6 L

Cast iron front axle provides the durability and strength required to support front end attachments and overcome rough terrain.

Fingertip activated **electric PTO** for smooth deck engagement

Hydro-Static foot pedal drive system

with cruise control allows for easy and smooth speed adjustment allowing you to set your own pace while mowing. (Not available on Lawn Tractor 17/42)

Kohler[®] single and twin cylinder engines provide power and performance from a name you can trust. Choose the engine best suited to meet your needs and preferences with robust engine options ranging from 17 hp to 25 hp.

Powered h

Operator comfort is ensured with an **angled steering wheel** and a 15" high-back seat that can be moved forward or back to accommodate operators of varying heights.

Easy-to-use levers and controls make mowing a breeze while a wide step through design allows for easy access to and from the operating position.

Forward ground speed of 5.5 mph and 2.5 mph in reverse cut down on mowing time.

Industry leading 10" turning radius for optimum maneuverability and navigation around trees, flower beds and other obstacles. (*Not available on Lawn Tractor 17/42*)



Wide selection of available attachments

including a snow blade, snow thrower, snow cab, dozer blade, scoop, cultivators and more. (some attachments are not available for every model)



Large capacity baggers simplify clean-up of leaves, debris and grass clippings for quick, efficient landscape perfection. Other available attachments and accessories allow users to get the most out of their unit all-year long. The same demanding standards for high-quality American craftsmanship assures you versatile attachments are designed to provide lasting performance you can rely on for generations to come.



3-BAG POWERED BAGGER:

- 9-bushel capacity
- Heavy-duty cloth bags
- High output grass pump
- · Easy deck mount spindle-driven fan
- Compatible with Zoom XL and Max Zoom series

NON-POWERED BAGGER:

- 6-bushel capacity
- Geometric shape generates increased air/grass velocity
- Power result without a grass pump assist
- Compatible with Zoom series





48" TOW DILIG AFRATOR

- Opens soil to water, air, and nutrients for improved root growth and overall lawn health.
- 48" weight tray holds up to 175 lbs. for greater soil penetration.
- All eight aerator knife spools are galvanized to resist rust.
- 10" X 4" pneumatic tires foster smooth transport



36" POLY ROLLER

- Provides versatility that can be utilized for multiple applications around the yard such as packing down new seed or leveling uneven ground.
- Lightweight when empty for easy transport and storage.
- Poly construction for rust resistance.
- 18" diameter X 36" wide



■ CONVERTIBLE DUMP CART

- Versatile cart that's perfect for accomplishing numerous chores including hauling debris, mulch, tools, and more!
- Converts easily to function as a tow or push cart
- 500 lb. capacity for heavy loads
- 30.5" X 4" X 11" bed size
- Durable poly construction means the cart is easy to clean and rust resistant
- Large pneumatic tires make it easy to maneuver



CHROME WHEEL COVERS



OPERATOR CONTROLLED CHUTE BAFFLE



SUNSHADE



HITCH KIT



FLEX TEND™ SHOULDER SUPPORT SYSTEM



DETHATCHER



15-GALLON SPRAYER



SPREADER

CLASSIC LM For more than 30 years this classic has made the cut.





CHORE

No landscape is perfectly beautiful until the fine details have been taken care of. Ariens is proud to offer a full line of Chore and Finishing products built to help homeowners do just that – create a flawless, well-manicured landscape. Every Ariens Chore and Finishing product comes supported by warranties you can feel confident in. And best of all, each product is easy to operate and maintain for years of reliable performance. Create the landscape you want at a price you can afford with Ariens dependable Chore and Finishing products.





POWER BRUSHES

Ariens multi-functional, all-season Power Brushes are capable of removing snow up to 6" deep along with other debris including sand, dirt, and gravel from sidewalks, driveways, and decorative surfaces such as patio brick or cobblestone. It's also excellent for removing gravel from lawns and dethatching.



All-season Subaru® engine with electric start for optimal performance in all weather conditions (12V key start on 926515)



40-degree brush head rotation with an operator controlled pivot lock makes changing the brush head direction simple



Height adjustment system accommodates various surfaces while reducing brush wear and tear



PRESSURE WASHERS



FEATURES: 3000 & 3300 PSI

- 169 211cc Subaru* 4 Cycle OHV Engine with idle-down automatically adjusts the power output to save fuel
- 2.6 3.0 GPM Professional Grade CAT Pump with ceramic plungers
- Professional-Grade Quick-Connect 0°, 15°, 25°, 40°short and long range soap nozzles offer washing versatility (15°is not included on 3000 psi model)
- 30 ft. hose Steel braided on 3300 PSI model and Powerflex on 3000 PSI model
- 12" NEVER FLAT tires maneuver easily on rough terrain (Foam filled on 3300 psi model, plastic rim on 3000 psi model)

FEATURES: 2800 PSI

- Maintenance Free 2.5 GPM Axial Cam Pump
- Powerful 208cc Ariens AX Engine
- Precision 0, 25, 40-degree and short and long range soap nozzles included
- Wheel barrow frame with quick release handle
- 10" Steel Rim Never Flat Wheels
- 25' Non-Marring M22 High Pressure Hose

PRECISION TILLERS

Eliminate pesky weeds and cultivate nutrient rich soil with an Ariens Precision Tiller. Choose from a rear or front tine model to suit your individual garden size and needs.



FEATURES:

- Chain drive transmission for superior torque
- 12", 22", and 24" tilling widths
- Heat treated tines for long-lasting durability
- 6" tilling depth
- Folding handlebars for quick, easy storage
- Adjustable rubber wheels and depth stake



GENERATORS



Whether you're tailgating, camping, on the jobsite, or searching for peace of mind in the event of an emergency or power outage, Ariens has your back with a lineup of dependable generators.

FEATURES:

2000i Inverter

- 2,000 starting watts and 1,600 running watts
- Powerful 79 cc Ariens engine
- Provides clean power that's safe for sensitive electronics such as computers, televisions, and cell phones
- Electronic Smart Control matches power output to the load requirement to optimize fuel consumption and reduce noise
- 1.1 gal. fuel capacity for up to 9.7 hours of operation with a 25% load
- Lightweight and easy to transport at just 46 lbs.
- 2 120V, 20 amp outlets and 1 12V DC outlet

5000 Watt Generator

- 6,250 starting watts and 5,000 running watts
- Powerful 287 cc Subaru® engine
- 6 gal. fuel capacity for up to 12.5 hrs. of operation with a 50% load
- 4 120V outlets, 1-240V 30 A outlet with circuit breaker protection
- Automatic voltage regulator for clean, efficient operation

7500 Watt Generator

- 9,375 starting watts and 7,500 running watts
- Powerful 390 cc Honda GX Engine with electric start
- 8 gal. fuel capacity provides up to 12 hrs. of power with a 50% load
- 4 120V outlets, 1 240V 30 A outlet with circuit breaker protection
- Automatic voltage regulator drives clean, efficient operation
- Analog hour meter allows the user to easily track time between regular maintenance





STRING TRIMMER



EDGER



FEATURES:

- Laterally adjustable front wheel for trimming
- 4-point cutting height adjustment
- All-steel design ensures strength and durability
- Curb hop feature allows the right rear wheel to adjust vertically for edging along curbs
- Robust, ergonomic T-handle optimizes operator comfort and control



Log Splitter

Centrally-located controls and an open operating zone allows users to work from either side of an Ariens Log Splitter reducing operator fatigue and conserving energy while dividing work time in half.

FEATURES:

Choose from **3 available models** to suit your needs and preferences — 22, 27, or 34-ton.

Powerful Subarus engines perform efficiently with minimal noise and emissions

Horizontal and vertical splitting positions provide flexibility for splitting large, heavy logs

Integrated log cradle prevents logs from falling to the ground



Cast iron hydraulic pumps, high temperature return line hoses, and industrial couplings mean each unit is built to last



A tapered wedge design requires less tonnage while splitting logs faster and more efficiently



Centrally located controls

and an open operating zone allow for operation from both sides of the machine. The operator doesn't have to step around a wheel/fender when they load and unload logs.



ALL-PURPOSE VAC

Easily collect litter, leaves, dirt, and other debris with a high-powered all-purpose Vac.

FEATURES:

Robust **Subaru**® **190cc** overhead cam engine

Push/self-propelled drive system

1775 cfm of suction power

Durable **12-gauge steel fan** housing

Generous **31-inch** clearing width

6 cu ft. /43 gal. collection capacity

Large 14-inch solid rubber wheels provide maneuverability

Easy to empty, **zipperless** wire formed bag





Rite-Hite Handlebar™

provides 5 operating positions for a comfortable working experience



13.5-inch steel, 5-blade impeller with serrated edges reduces debris



Suction height adjustment with 17 positions ranging from 0 to 5"



PRODUCT NAME	Max Zoom® 60	Max Zoom® 52	Max Zoom® 48	Zoom XL® 54
MODEL NUMBER	991087	991086	991085	915173
ENGINE	Kohler® KT 740 Pro Twin	Kohler® KT 730 Twin	Kohler® KT 725 Twin	Kohler® KT 735 Twin
HORSEPOWER*	25 hp	23 hp	22 hp	24 hp
DISPLACEMENT (CC)	725 cc	725 cc	725 cc	725 cc
DRIVE SYSTEM	Hydro-Gear® ZT-3100 Transaxles	Hydro-Gear® ZT-3100 Transaxles	Hydro-Gear® ZT-3100 Transaxles	Hydro-Gear® ZT-2800 Transaxles
FUEL CAPACITY Gallons (Liters)	6 Gallons (22.7L)	6 Gallons (22.7L)	6 Gallons (22.7L)	3.8 Gallons (14.4L)
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	8 mph/4 mph	8 mph/4 mph	8 mph/4 mph	6.5 mph /3 mph
STARTER	Electric	Electric	Electric	Electric
DECK				
DECK MATERIAL	10 ga w/ .25" Spindle Reinforcement	10 ga w/ .25" Spindle Reinforcement	10 ga w/ .25" Spindle Reinforcement	10 ga w/ Doubler Plate
DECK CONSTRUCTION	Welded	Welded	Welded	Welded
NUMBER OF SPINDLES	3	3	3	3
BLADE TIP SPEED (FPM)	18,000	18,000	18,000	16,950
SPINDLE MATERIAL	Cast Iron	Cast Iron	Cast Iron	Aluminum
SPINDLE SHAFT	Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Ball Bearing	Ball Bearing	Ball Bearing	Sealed
DECK DRIVE	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Ogura® GT1A	Electric Warner®
DECK LIFT SYSTEM	Foot Operated	Foot Operated	Foot Operated	Foot Operated
CUTTING WIDTH	60"	52"	48"	54"
CUTTING HEIGHTS	1"- 5"	1"- 5"	1"- 5"	1.5"- 4.5"
CUTTING POSITIONS	9	9	9	7
WHEELS				
FRONT AXLE	Fixed	Fixed	Fixed	Fixed
FRONT	13" x 5"- 6"	13" x 5"- 6"	13" x 5"- 6"	11" x 4"- 5"
REAR	20" x 10"- 10"	20" x 10"- 10"	20" x 10"- 10"	20" x 10"- 8"
EATURES				
HOOD	N/A	N/A	N/A	Standard
HEADLIGHTS	Optional	Optional	Optional	Optional
SEAT	High Back w/ Seat Springs, Lever Adjust & Arm Rests	High Back w/ Seat Springs, Lever Adjust & Arm Rests	High Back w/ Seat Springs, Lever Adjust & Arm Rests	High Back w/ Seat Springs, Lever Adjust & Arm Rests
HOUR METER	Standard	Standard	Standard	Standard
DIMENSIONS				
WEIGHT (LBS)	853	832	823	645
LENGTH	74.5"	74.5"	71.5"	69"
WIDTH	62.8" (w/o chute)	55.5" (w/o chute)	50" (w/o chute)	64" (w/ chute)
HEIGHT	42"	42"	42"	42"
WARRANTY				
MACHINE	3 Ye	ear Limited Consumer, 1 Year Limited Commer	rcial	
DECK SHELL & FRAME		5 Year Limited		
ATTACHMENTS & ACCESSORIES		2.12. 2		
OPTIONAL OPTIONAL	Sprayer, Spreader, Dump Cart, Wheel Covers,	t, Bagger Mount Kit, Trailer Hitch Kit, 36" Poly Ro Headlight Kit, Suspension Seat Kit, Lawn Stripin, Jlder Support System, Operator Controlled Chute	ng Kit, Discharge Cover Kit, Vacuum Baffle Kit,	3-Bucket Powered Bagger Kit, Mulchin; Spreader, Dump Cart, Whee Supp

Zoom XL® 48	Zoom XL® 42	Zoom® 50	Zoom® 42	Zoom® 34	
915165	915163	915161	915159	915189	
Kohler® KT 725 Twin	Kohler® KT 715 Twin	Kohler® KT 725 Twin	Kohler® KT 715 Twin	Briggs & Stratton® Twin Cylinder	
22 hp	20 hp	22 hp	20 hp	16 hp	
725 cc	725 cc	725 cc	725 cc	656 cc	
Hydro-Gear® ZT-2800 Transaxles	Hydro-Gear® ZT-2800 Transaxles	Hydro-Gear® EZT Transaxles with 1" Axle Shafts	Hydro-Gear® EZT Transaxles with 1" Axle Shafts	Hydro-Gear® EZT Transaxles with 1" Axle Shafts	
3.8 Gallons (14.4L)	3.8 Gallons (14.4L)	2.0 Gallons (7.5L)	2.0 Gallons (7.5L)	2.0 Gallons (7.5L)	
6.5 mph /3 mph	6.5 mph /3 mph	6 mph/3 mph	6 mph/3 mph	6 mph/3 mph	
Electric	Electric	Electric	Electric	Electric	
10 ga w/ Doubler Plate	10 ga w/ Doubler Plate	12 ga	12 ga	12 ga	
Welded	Welded	Stamped	Stamped	Stamped	
3	3	3	3	2	
16,800	17,000	17,800	17,000	17,500	
Aluminum	Aluminum	Steel	Steel	Steel	
Steel	Steel	Steel	Steel	Steel	
Sealed	Sealed	Sealed	Sealed	Sealed	
Belt	Belt	Belt	Belt	Belt	
Electric Warner®	Electric Warner®	Electric Warner®	Electric Warner®	Electric Warner®	
Foot Operated	Foot Operated	Foot Operated	Foot Operated	Foot Operated	
48"	42"	50"	42"	34"	
1.5"- 4.5"	1.5"- 4.5"	1.5"- 4.5"	1.5"- 4.5"	1.5"- 4.5"	
7	7	7	7	7	
Fixed	 Fixed	Fixed	Fixed	Fixed	
11" x 4"- 5"	11" x 4"- 5"	11" x 4"- 5"	11" x 4"- 5"	11" x 4"- 5"	
20" x 10"- 8"	20" x 8"- 8"	18" x 9.5"- 8"	18" x 8.5"- 8"	18" x 6.5"- 8"	
20 X 10 - 0	20 10 - 0	10 X 3.3 - 0	10 X 0.3 - 0	10 X 0.3 - 0	
Standard	Standard	Standard	Standard	Standard	
Optional	Optional	N/A	N/A	N/A	
High Back w/ Seat Springs, Lever Adjust & Arm Rests	High Back w/ Seat Springs, Lever Adjust & Arm Rests	High Back w/ Seat Springs, Lever Adjust	High Back w/ Seat Springs, Lever Adjust	Mid Back w/ Seat Springs	
Standard	Standard	N/A	N/A	N/A	
630	615	475	440	425	
69"	69"	64"	64"	64"	
58" (w/ chute)	52" (w/ chute)	62" (w/ chute)	54" (w/ chute)	42" (w/ chute)	
42"	42"	43"	43"	37"	
	·•				
3 Year Limited Consumer			3 Year Limited Consumer		
5 Year Limited		5 Year Limited			
Trailer Hitch Kit, 36" Poly Roller, 48" Aerat ers, Sun Shade, Headlight Kit, 54" Snow Bl stem, Seat Cover, Mower Cover, Engine Gu	ade, FlexTend™ Shoulder		Kit, Mulching Kit, Trailer Hitch Kit (Standard on 4 on Sprayer, Spreader, Dump Cart, Wheel Covers, Seat Cover, Mower Cover, Arm Rest Kit		

PRODUCT NAME	Garden Tractor 54	Lawn Tractor 54	Lawn Tractor 48	Lawn Tractor 46	Lawn Tractor 20/42	Lawn Tractor 17/42
MODEL NUMBER	936096	936097	936098	936099	936100	936101
ENGINE	Kohler® KT 740 V-Twin	Kohler® KT 740 V-Twin	Kohler® KT 725 V-Twin	Kohler® KT 725 V-Twin	Kohler® Courage Single	Kohler® Courage Single
HORSEPOWER*	25 hp	25 hp	22 hp	22 hp	20 hp	17 hp
DISPLACEMENT (cc)	725 cc	725 cc	725 cc	725 cc	597 сс	597 сс
DRIVE SYSTEM	Hydrostatic Foot Pedal	Hydrostatic Foot Pedal	Hydrostatic Foot Pedal	Hydrostatic Foot Pedal	Hydrostatic Foot Pedal	6 Speed Gear Drive
FUEL CAPACITY Gallons (Liters)	4.0 Gallons (15.2L)	3.0 Gallons (11.4L)	3.0 Gallons (11.4L)	2.5 Gallons (9.5L)	2.5 Gallons (9.5L)	1.5 Gallons (5.6L)
GROUND SPEED (APPROX. MPH) (FORWARD/REVERSE)	5.5 mph/2.5 mph	5.5 mph/2.5 mph	5.5 mph/2.5 mph	5.5 mph/2.5 mph	5.5 mph/2.5 mph	5.5 mph/2.5 mph
STARTER	Electric (Bendix)	Electric (Bendix)	Electric (Bendix)	Electric (Bendix)	Electric (Bendix)	Electric (Bendix)
DECK						
DECK MATERIAL	10 ga	11 ga	11 ga	12 ga	12 ga	12 ga
DECK CONSTRUCTION	Stamped	Stamped	Stamped	Stamped	Stamped	Stamped
NUMBER OF SPINDLES	3	3	3	2	2	2
BLADE TIP SPEED (FPM)	19,000 (max)	19,000 (max)	19,000 (max)	19,000 (max)	19,000 (max)	19,000 (max)
SPINDLE MATERIAL	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
SPINDLE SHAFT	Steel	Steel	Steel	Steel	Steel	Steel
SPINDLE BEARINGS	Greaseable	Ball Bearing	Ball Bearing	Sealed	Sealed	Sealed
DECK DRIVE	Belt	Belt	Belt	Belt	Belt	Belt
DECK ENGAGEMENT	PTO Electric	PTO Electric	PTO Electric	PTO Electric	PTO Electric	PTO Electric
DECK LIFT SYSTEM	Manual, Spring Assist	Manual, Spring Assist	Manual, Spring Assist	Manual, Spring Assist	Manual, Spring Assist	Manual, Spring Assist
CUTTING WIDTH	54"	54"	48"	46"	42"	42"
CUTTING HEIGHTS	1.5" - 4"	1.5" - 4"	1.5" - 4"	1.5" - 4"	1.5" - 4"	1.5" - 4"
CUTTING POSITIONS	7	10	10	10	10	6
TURNING RADIUS	10"	10"	10"	10"	10"	16"
WHEELS	10	10	10	10	10	10
FRONT AXLE	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron	Cast Iron
FRONT	16" x 6.5"- 6"	15" x 6" - 6"	15" x 6" - 6"	15" x 6" - 6"	15" x 6" - 6"	15" x 6"- 6"
REAR	23" x 10.5"- 12"	20" x 8" - 8"	20" x 8" - 8"	20" x 8" - 8"	20" x 8" - 8"	20" x 8"- 8"
FEATURES	20 X 1010 12	20 X 0	20 X 0 0	20 X 0 0	20 %0 0	ZU NO U
HOOD	Predator	Predator	Predator	Predator	Predator	Predator
HEADLIGHTS	Standard	Standard	Standard	Standard	Standard	Standard
SEAT	High Back 15", Slide	High Back 15", Slide	High Back 15", Slide	High Back 15", Slide	High Back 15", Slide	Mid Back 11", Slide
HOUR METER	Standard	Standard	Standard	Standard	Standard	Standard
DIMENSIONS	Standard.	otanaa.a	Standard .	Standa d	Standard	otaniana
WEIGHT (LBS)	577	503	488	450	441	361
LENGTH	73.75"	72.75"	72.75"	72.75"	72.75"	72.75"
WIDTH	58.5"	58.5"	52.5"	49.5"	45"	45"
HEIGHT	47"	47"	46"	46"	46"	46"
WARRANTY	71	T/	10	10	⁺⁰	1 70
MACHINE			2 Vaar Limit	ed Consumer		
ATTACHMENTS & ACCESSORIES			Z 1641 LIIIIII	ou ouisuniti		
OPTIONAL	Bagger Kit, Mulching Kit, S Snow Cab, Tractor Weight Kit, Dozer Blad	Scoop, Sun Shade,	Bagger Kit, Mulching M	(it, Snow Blade, Snow Throw	er, Snow Cab, Tractor Scoop,	, Sun Shade, Weight Kit

PRODUCT NAME	Classic LM 21	Classic LM21 S	Classic LM21 SW
MODEL NUMBER	911170	911193	911194
ENGINE	Kohler® XT-7.75		
HORSEPOWER*	N/A	N/A	N/A
DISPLACEMENT (cc)	173 cc	179 cc	179 cc
DRIVE SYSTEM	Push	Infi-Speed® Variable Speed Drive	Infi-Speed® Variable Speed Drive
FUEL CAPACITY GALLONS (LITERS)	0.37 Gallon (1.4L)	0.48 Gallon (1.8L)	0.48 Gallon (1.8L)
GROUND SPEED (APPROX. MPH) (FORWARD/ REVERSE)	N/A	4 mph	4 mph
STARTER	Recoil	Recoil	Recoil
DECK			
DECK MATERIAL	14 ga	14 ga	14 ga
DECK CONSTRUCTION	Stamped	Stamped	Stamped
NUMBER OF Blades	1	1	1
BLADE TIP Speed (FPM)	18,000	18,000	18,000
DECK DRIVE	Direct	Direct	Direct
DECK Engagement	Bail	Bail	Bail
DECK LIFT System	4-Point	4-Point	4-Point
CUTTING WIDTH	21"	21"	21"
CUTTING HEIGHTS	1" - 3.25"	1" - 3.25"	1" - 3.25"
CUTTING Positions	6	6	6
WHEELS			
FRONT AXLE	Straight	Straight	Swivel
FRONT	7.5"	7.5"	7.5"
REAR	10.5"	10.5"	10.5"
DIMENSIONS			
WEIGHT (LBS)	100	104	121
LENGTH	61.5"	61.5"	61.5"
WIDTH	23"	23"	23"
HEIGHT	38"	38"	38"
WARRANTY			
MACHINE		ar Limited Cons	umer
ATTACHMENTS & ACC	ESSORIES		
STANDARD	Bagg	er Kit, Mulching	Plug
OPTIONAL	1	er, Dethatcher, t, Swivel Wheel	-

PRODUCT NAME	Ariens Razor™ Push	Ariens Razor™ Self Propelled	Ariens Razor™ Self Propelled	Ariens Razor™ Electric Start	Ariens Razor™ Electric Start	Ariens Razor™ BBC	Ariens Razor™ BBC
MODEL NUMBER	911173	911188	911175	911190	911179	911189	911177
ENGINE	Ariens	Subaru®	Ariens	Subaru®	Ariens	Subaru®	Ariens
HORSEPOWER*	N/A	N/A	N/A	N/A	N/A	N/A	N/A
DISPLACEMENT (cc)	159 cc	175 cc	159 cc	175 cc	159 cc	175 cc	159 cc
DRIVE SYSTEM	Push	Variable Speed Rear Wheel Drive					
FUEL CAPACITY GALLONS (LITERS)	0.26 Gallon (1L)	0.26 Gallon (1L)	0.26 Gallon (1L)	0.26 Gallon (1L)	0.26 Gallon (1L)	0.26 Gallon (1L)	0.26 Gallon (1L)
GROUND SPEED (APPROX. MPH) FWD/REV	N/A	0-3.2 mph					
STARTER	Recoil	Recoil	Recoil	Electric Start	Electric Start	Recoil	Recoil
DECK							
DECK MATERIAL	14 ga	14 ga	14 ga	14 ga	14 ga	14 ga	14 ga
DECK CONSTRUCTION	Stamped	Stamped	Stamped	Stamped	Stamped	Stamped	Stamped
NUMBER OF Blades	1	1	1	1	1	1	1
BLADE TIP SPEED (FPM)	17,000	17,000	17,000	17,000	17,000	17,000	17,000
DECK DRIVE	Direct	Direct	Direct	Direct	Direct	Direct	Direct
DECK Engagement	Bail	Bail	Bail	Bail	Bail	Bail	Bail
DECK LIFT SYSTEM	Single Point	Single Point	Single Point	Single Point	Single Point	Single Point	Single Point
CUTTING WIDTH	21"	21"	21"	21"	21"	21"	21"
CUTTING HEIGHTS	1" - 4"	1" - 4"	1" - 4"	1" - 4"	1" - 4"	1" - 4"	1" - 4"
CUTTING POSITIONS	7	7	7	7	7	7	7
WHEELS							
FRONT AXLE	Straight	Straight	Straight	Straight	Straight	Straight	Straight
FRONT	8.375"	8.375"	8.375"	8.375"	8.375"	8.375"	8.375"
REAR	8.375"	8.375"	8.375"	8.375"	8.375"	8.375"	8.375"
DIMENSIONS							
WEIGHT (LBS)	94	97	97	106	106	111	111
LENGTH	70"	70"	70"	70"	70"	70"	70"
WIDTH	21.5"	21.5"	21.5"	21.5"	21.5"	21.5"	21.5"
HEIGHT	47"	47"	47"	47"	47"	47"	47"
WARRANTY							
MACHINE			3 Yea	ar Limited Cons	umer		
ATTACHMENTS & ACCES	SORIES						
STANDARD			Bagg	er Kit, Mulching	Plug		
OPTIONAL				N/A			

	GENERATOR		
PRODUCT NAME	INVERTER	5000 WATT	7500 WATT
MODEL NUMBER	986057	986054	986055
PERFORMANCE/SPECIFICATIONS			
RUNNING (CONTINUOUS) WATTS	1600	5000	7500
STARTING WATTS	2000	6250	9375
RATED VOLTAGE	120 V	120 / 240 V	120 / 240 V
RATED FREQUENCY	60 HZ	60 HZ	60 HZ
RATED AMPS AT 12 V DC	8.3 A	N/A	N/A
RUN TIME AT 50% LOAD	6 HRS	12.5 HRS	12 HRS
ENGINE			
MANUFACTURER	ARIENS	SUBARU® EX	HONDA® GX
HORSEPOWER/DISPLACEMENT	79CC	287CC	390CC
STARTING SYSTEM	RECOIL	RECOIL	RECOIL/ELECTRIC
FUEL CAPACITY	1.1 GAL	6 GAL	8 GAL
LOW OIL SENSOR/SHUTDOWN	YES	YES	YES
OUTLETS AND CIRCUIT PROTECTION			
120 V AC	125V DUPLEX, 20 A	2 - 120V DUPLEX, 20 A GFCI	2 - 120V DUPLEX, 20 A GFCI
120 / 240 V AC	N/A	1 - 120V/240V TWIST LOCK 20 A	1 - 120V/240V TWIST LOCK 30 A
12 V DC	YES	N/A	N/A
CIRCUIT BREAKER/TYPE	PUSH BUTTON	PUSH BUTTON	PUSH BUTTON
OUTLET RAIN PROTECTION	N/A	RUBBER FLAPS	RUBBER FLAPS
INDICATORS			
LOW OIL INDICATOR LED	YES	N/A	N/A
OVERLOAD INDICATOR LED	YES	N/A	N/A
OUTPUT INDICATOR LED	YES	N/A	N/A
ANALOG HOUR METER	N/A	N/A	YES
SWITCHES AND CONTROL VALVES			
FUEL VALVE	YES	YES	YES
ENGINE ON/OFF	YES	YES	YES
AUTO IDLE	YES	N/A	N/A
СНОКЕ	MANUAL CHOKE	MANUAL CHOKE	MANUAL CHOKE
ALTERNATOR			
TYPE	INVERTER TYPE	BRUSH-TYPE	BRUSH-TYPE
VOLTAGE REGULATION	INVERTER ELECTRONIC	FREQUENCY- COMPENSATING AVR	FREQUENCY- COMPENSATING AVR
MODIFIED SINE WAVE	YES	N/A	N/A
CHASSIS			
ТҮРЕ	SUITCASE STYLE INJECTION MOLDED	HAND TRUCK FRAME	WHEEL BARROW FRAME
FRAME STRUCTURE	INJECTION MOLDED	TUBULAR FRAME - 1-1/4"	TUBULAR FRAME - 1-1/4
HANDLE TYPE	INJECTION MOLDED	FOLD-DOWN - 1-1/4"	FOLD-DOWN - 1-1/4"
WHEEL TYPE	N/A	10" X 3" SEMI-PNEUMATIC STEEL RIM	10" X 3" SEMI-PNEUMAT STEEL RIM
ADDITIONAL FEATURES			
50 FT 20 A CORD, 4 Plug extensions	N/A	YES	N/A
SPARK PLUG WRENCH	YES	N/A	N/A
DC BATTERY CLAMP CABLES	YES	N/A	N/A
PARALLEL KIT	YES - 20 AMP	N/A	N/A
DIMENSIONS			
OVERALL LENGTH (INCHES)	19.6"	24"	31"
OVERALL WIDTH (INCHES)	11.2"	21"	26"
OVERALL HEIGHT (INCHES)	17.9"	29"	29"
DRY WEIGHT (LBS)	46	166	189
ACCESSORIES/ATTACHMENTS			
	ADAPTERS - 30A/240V TO	DA TO 30 A, 30A/120V TO 30A 20A/240V, 20A/240V TO 30A, COVER, WHEEL KIT, PARALLEL	240V, 25 FT/30 A SPLITTEF
		OUTLIN, THILLE INIT, FARALLEL	THE THIRD DU AT LUG
WARRANTY	oons, denemmen		

	POWER BRUSHES					
MODEL NUMBER	POWER BRUSH 28	POWER BRUSH 36	HYDRO BRUSH 36			
MODEL NUMBER	921025	926057	926515			
ENGINE DISPLACEMENT	169CC	265CC	287CC			
ENGINE MFG	SUBARU®	SUBARU®	SUBARU®			
STARTING SYSTEM	120V/RECOIL	120V/RECOIL	12V/RECOIL			
CLEARING WIDTH	28 IN (71.2 CM)	36 IN (91.4 CM)	36 IN (91.4 CM)			
BRUSH DIAMETER	18" (46 CM)	25" (64 CM)	25" (64 CM)			
BRUSH WIDTH	28 IN (71.2 CM)	36 IN (91.4 CM)	36 IN (91.4 CM)			
BRUSH ROTATION ANGLE	40°	40°	40°			
BRUSH ROTATION CONTROL	REMOTE TRIGGER	REMOTE TRIGGER	REMOTE TRIGGER			
INTERLOCK CONTROL	NO	YES	YES			
TIRE SIZE	16 IN X 5 IN (41 X 12.7 CM)	16 IN X 6.5 IN (41 X 17 CM)	16 IN X 6.5 IN (41 X 17 CM)			
TIRE TYPE		DIRECTIONAL SNOW TREAD				
AXLE SYSTEM	AU	ITOMATIC TRACTION CONTR	OL			
FUEL TANK CAPACITY	3.4QT (3.6L)	5.7QT (6.1L)	5.7QT (6.1L)			
DRIVE TYPE	DISC-O-MATIC	DISC-O-MATIC	HYDROSTATIC			
SPEEDS: FORWARD And Rev	6 FORWARD/ 2 REVERSE	6 FORWARD/ 2 REVERSE	INFINITE			
WARRANTY	3-YEAR LIMITED CONSUMER/90-DAY LIMITED COMMERCIAL		ED CONSUMER D COMMERCIAL			
FEATURES AT A GLANCE						
HALOGEN HEADLIGHT	NO	STANDARD	STANDARD			
HANDWARMERS	NO	NO	STANDARD			
ELECTRIC START	STANDARD	STANDARD	STANDARD			
DIMENSIONS						
LENGTH	65" (165.1 CM)	72" (182.9 CM)	72" (182.9 CM)			
WIDTH	34" (86.4 CM)	44" (111.8 CM)	44" (111.8 CM)			
HEIGHT	44" (111.8 CM) 43" (109.2 CM) 43" (43" (109.2 CM)			
DRY WEIGHT (LBS)	230 (104.3 KG)	325 (147.4 KG)	335 (151.9 KG)			
ACCESSORIES						
	TURF CASTER KIT, TIRE CHAINS		ECTOR, TIRE CHAINS, HEAD, TURF CASTER KIT			

	LOG SPL	ITTERS			
PRODUCT NAME	22-TON LOG SPLITTER	27-TON LOG SPLITTER	34-TON LOG SPLITTER		
MODEL NUMBER	917011	917001	917002		
ENGINE	SUBARU®	SUBARU®	SUBARU®		
HORSEPOWER/ Displacement	4.5 HP/174 CC	5.7 HP/169 CC	7 HP/211 CC		
STARTING SYSTEM	RECOIL	RECOIL	RECOIL		
FUEL CAPACITY	.32 GAL	.95 GAL	.95 GAL		
HYDRAULIC CAPICITY	4.5 GAL (17 L)	4.5 GAL (17 L)	4.5 GAL (17 L)		
SPLITTING FORCE	22-TON	27-TON	34-TON		
CYLINDER CYCLE TIME- Sec	13	15	17		
LOG CAPACITY	25" (63.5 CM)	25" (63.5 CM)	25" (63.5 CM)		
HITCH COUPLER	2"	2"	2"		
MAXIMUM TOWING SPEED	45 MPH	45 MPH	45 MPH		
2-STAGE HYDRAULIC Pump	11 GPM	11 GPM	13 GPM		
CHASSIS	CONSUMER	PROFESSIONAL	PROFESSIONAL		
HORIZONTAL AND Vertical splitting	STANDARD	STANDARD	STANDARD		
OPEN OPERATING ZONE	STANDARD	STANDARD	STANDARD		
CENTRALLY LOCATED CONTROLS	STANDARD	STANDARD	STANDARD		
TAPERED WEDGE	STANDARD	STANDARD	STANDARD		
WHEEL FENDERS	OPTIONAL	STANDARD	STANDARD		
SAFETY CHAINS	STANDARD	STANDARD	STANDARD		
LOG CRADLE	STANDARD	STANDARD	STANDARD		
WORK TABLE	OPTIONAL	OPTIONAL	OPTIONAL		
JACK STAND WITH WHEEL	N/A	OPTIONAL	STANDARD		
HITCH HANDLE	STANDARD	STANDARD	STANDARD		
WHEELS					
REAR	4.8"/4.00 X 8"	4.8"/4.00 X 8"	4.8"/4.00 X 8"		
SERVICEABLE AXLES	N/A	STANDARD	STANDARD		
DIMENSIONS			<u> </u>		
WEIGHT (LBS)	367	500	525		
LENGTH	84.68"	86.25"	86.25"		
WIDTH	37.58"	38.25"	38.25"		
HEIGHT	46.25"	46.50"	46.50"		
ACCESSORIES/ATTACHMENT	TRAILER TAIL LIGHTS, TRAILER LIGHT MOUNTING BRACKET, LICENSE PLATE HOLDER, ENGINE COVER, CYLINDER HANDLE, MUFFLER GUARD, LOG SPLITTER COVER, JACK STAND WITH WHEEL, WORK TABLE, FENDERS				
WARRANTY					

	TILLERS	
PRODUCT NAME	FRONT TINE TILLER	REAR TINE TILLER
ARIENS PART NUMBER	902032	901028
ENGINE	SUBARU®	SUBARU®
HORSEPOWER	6 HP / 169 CC	6 HP / 169 CC
DRIVE SYSTEM	ROLLER CHAIN	CHAIN/GEAR
FUEL CAPACITY - GALLONS (LITERS)	0.89 GAL (3.4L)	0.89 GAL (3.4L)
TINE SPEED	118 RPM	190 RPM
STARTER	RECOIL	RECOIL
DECK		
TILLING WIDTH	24"/22"/12"	17"
TINE DIAMETER	12"	13"
TILLING DEPTH	6"	6.5"
HANDLE	FOLDABLE	ADJUSTABLE
WHEELS		
TIRE SIZE	1.75" X 8" SEMI-PNEUMATIC	13" X 5" X 6" PNEUMATIC
DIMENSIONS		
WEIGHT (LBS)	115	230
LENGTH	27.5"	48"
WIDTH	25"	24.5"
HEIGHT	33.5"	34.5"
WARRANTY		
	2 YEAR LIMITE	D CONSUMER
FEATURES		
SAFETY CLUTCH HANDLE	STANDARD	STANDARD
FORWARD TILL	STANDARD	STANDARD
REVERSE TILL	N/A	YES
DUAL ROTATING TINES	N/A	STANDARD
DEPTH STAKE	STANDARD	STANDARD
BUMPER	N/A	STANDARD

MODEL NUMBER 986005 986006 986007	PRESSURE WASHERS				
RATED MAX, PECSURE - PSI 2800 PSI 3000 PSI 300 PSI 3000 P	PRODUCT NAME	2800 PSI PRESSURE WASHER	3000 PSI PRESSURE WASHER	3300 PSI PRESSURE WASHER	
RATED MAX. PRESSURE - PSI	MODEL NUMBER	986005	986006	986007	
RATED MAX. FLOW - GPM WAIRE REMPERATURE MANUFACTURER ARIENS AX 179CC 169CC 169CC 211CC STARTING SYSTEM FUEL CAPACITY 0.68 CAL 0.95 GAL 179C 179C 169CC 169CC 211CC 179CC 169CC 211CC 179CC 169CC 211CC 179CC 169CC 211CC 179CC 169CC 169CC 211CC 179CC 169CC 211CC 179CC 169CC 211CC 179CC 169CC 211CC 179CC 169CC 169CC 211CC 179CC 169CC 211CC 179CC 169CC 211CC 179CC 179CC					
WATER TEMPERATURE PROBLE WHORSPOWER/DISPLACEMENT 179CC 169CC 211CC STARTING SYSTEM RECOIL PRECIDE PUBLIC CAPACITY 0.68 GAL 0.95 GAL 0.95 GAL 0.95 GAL VES NAA NAA VES PUBLIC CAPACITY 0.68 GAL 0.95 GAL 0.95 GAL 0.95 GAL VES NAA NA VES PUBLIC CAPACITY 0.68 GAL 0.95 GAL O.95 GAL O.95 GAL O.95 GAL VES PUBLIC CAPACITY O.95 GAL O.95 GAL O.95 GAL O.95 GAL O.95 GAL O.95 GAL VES PUBLIC CAPACITY O.95 GAL O.95	RATED MAX. PRESSURE - PSI	2800 PSI	3000 PSI	3300 PSI	
ENGINE MANUFACTURER MARUFACTURER MARUFACTURER MARUFACTURER 179CC 169CC 211CC STARTING SYSTEM 0.68 GAL 0.95 GAL VES DUMP MANUFACTURER TIT CAT PUMPS 3-PISTON AXIAL CAM, BRASS HEAD (EZ-START & RUN DRY PROTECTION) 250 HOUR MINIMUM TYPE 3-PISTON AXIAL CAM, BRASS HEAD (EZ-START & RUN DRY PROTECTION) 250 HOUR MINIMUM YES CHEMICAL HURCTOR CHEMICAL HURCH H	RATED MAX. FLOW - GPM	2.5 GPM		3.0 GPM	
MANUFACTURER #ORSEPOWER/DISPLACEMENT #ORSEPOWER/DISP	WATER TEMPERATURE		COLD WATER		
HORSEPOWER/DISPLACEMENT 179CC 169CC 211CC 21					
STARTING SYSTEM FUEL CAPACITY O. 68 GAL O. 95 GAL O. 96 GAL O. 97 GAL O. 97 GAL O. 97 GAL O					
FUEL CAPACITY O.68 GAL O.95 GAL O		1/9CC		211CC	
ENGINE IDLE DOWN INVA INVA INVA INVA INVA INVA INVA IVES PUMP MANUFACTURER TITI CAT PUMPS 3-PISTON AXIAL CAM, BRASS HEAD (EZ-START & RUN DRY PROTECTION) 250 HOUR MINIMUM 500 HOUR MINIMUM THERMAR RELIEF VALVE CHEMICAL INJECTOR LOW PRESSURE VENTURI LOW PRESSURE VENTURI LOW PRESSURE VENTURI LOW PRESSURE VENTURI CHASSIS WHEEL BARROW - 1-1/4 TUBING QUICK-RELEASE FOLD-DOWN HANDLE FRAME STYLE WHEEL TYPE 10° X 3° FOAM FILLED RUBBER FROUCH RELEASE FOLD-DOWN HANDLE SHORT/HITCH-PIN AXLE SHORT/HITCH-PIN BAILED, NON-MARRING GREY, M22 COUPLERS COUPLERS COUPLERS TRIGGER/GUN ARIENS FRONT ENTRY, M22-AN INLET, CHROME PLATED TUBING, OVER-MOLD GRIP AREAS, REMOVEDLE ANDLE TOWN COUPLERS SPRAY WAND ARIENS FRONT ENTRY, M22-AN INLET, CHROME PLATED TUBING, OVER-MOLD GRIP AREAS, REMOVEDLE ANDLE COUNTECT COUPLER ON-BOARD DETERRENT COUPLERS SOAP 3 STANDARD OG NOZZLES (0°, 25°, 40°) OUF ROAL LENGTH (INCHES) DOW PRESSSURE NOZZLES SOAP SOAP SOAP BLASTER SIPHONING HOSE WITH FILTER DIMENSION OVERALL LENGTH (INCHES) DRY WEIGHT (UBS) 75 98 105 G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SCALE RE NOZZLE, POWERFLEX PRESSURE WASHER NOSE, CAT HEAVY-DUTY PRESSURE WASHER FOR FORESSONAL READED PRESSURE WASHER FOR FORESSONAL READED PROSSURE WASHER FOR FORESSONA					
LOW OIL SENSOR N/A N/A N/A N/A YES PUMP MANUFACTURER TITI CAT PUMPS TYPE 3-PISTON AXIAL CAM, BRASS HEAD (EZ-START & RUIN DRY PROTECTION) 5-00 HOUR MINIMUM TYES CHEMICAL INJECTOR CHASSIS WHEEL BARROW - 1-1/4 TUBING QUICK-RELEASE FOUD-DOWN HANDLE UN'S 3" FOAM FILLED RUBBER STELE RIM SHORT/HITCH-PIN THERME STYLE 10" X 3" FOAM FILLED RUBBER STELE RIM SHORT/HITCH-PIN SHORT/HITCH-PIN 12" X 3" NEVER FLAT RUBBER RUBBER STEEL RIM RUBBER STEEL RIM SHORT/HITCH-PIN SHORT/HITCH-PIN SHORT/HITCH-PIN AXLE ARIENS FRONT ENTER, M22-M INLET, CHROME PLATED, M22 COUPLERS COUPLERS TUBING, OVER-MOLD GRIP AREAS, REMOVABLE ASSIST HANDLE 21" CHROME PLATED, M22 CONNECTION, STANDARD QC COUPLER 3 STANDARD QC NOZZLES (0", 25", 40") CONNECTION, STANDARD QC COUPLER NO NO 10", 15", 25", 40") SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER DIMERSION OVERALL LENGTH (INCHES) DOVERALL LENGTH (INCHES) OVERALL					
PUMP MANUFACTURER TTYPE 3-PISTON AXIAL CAM, BRASS HEAD (EZ-START & RUN DRY PROTECTION) 250 HOUR MINIMUM 500 HOUR MINIMUM 500 HOUR MINIMUM FRAME RELIEF VALVE CHEMICAL INJECTOR CHASSIS WHEEL BARROW - 1-1/4 TUBING QUICK-RELEASE FOLD-DOWN HANDLE 10" X 3" FOAM FILLED RUBBER STEEL RIM SHORT/HITCH-PIN 10" X 3" FOAM FILLED RUBBER STEEL RIM ADDITIONAL FEATURES 11/4" X 25', PVC OUTER SKIN, YARN BRADDED, NON-MARRING GREY, M22 COUPLERS TRIGGER/GUN ARIENS FRONT ENTRY, M22-M INLET, CHROME PLATED TUBING, QUICK CONNECT COUPLERS 12" STAINLESS STEEL, M2 CONNECT COUPLERS SPRAY WAND 12" CHROME PLATED TUBING, QUE CONNECTION, STANDARD QUE CONNECTION, STANDARD QUE COUNTER SKIN, STEEL, M2 CONNECT COUPLERS (0", 25", 40") 3 SANDARD OR NOZZLES (0", 25", 40") 3 QUICK CONNECT NOZZLES (0", 25", 40") 4 QUICK CONNECT NOZZLES (0", 25", 40") 5 QUERALL WIDTH (INCHES) 5 QUERALL KEICH NO CALLER POWER FLEX PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWER FLEX PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWER FLEX PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWER FLEX PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWER FLEX PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWER FLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUER 5 ON COUNTER, SHANDAND NON DOWER SENSIN HANDE 6 G-NEL CHARM, SO SEAR PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWER FLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUER 6 NEL CHARM, SO SHANDAND, ON COUNTING PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWER FLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER OWER GUERO WINDOW AND SIDING BRUSH, 18" TELESCOPPING WAND, 9" EXTENSION WAND, NIKHOOW AND SIDING BRUSH, 19" TELESCOPPING WAND, 9" EXTENSION WAND, NIKHOOW AND SIDING BRUSH, 19" TELESCOPPING WAND, 9" EXTENSION WAND, NIKHOOW AND SIDING BRUSH, 19" TELESCOPPING WAND, 9" EXTENSION WAND, NIK					
MANUFACTURER TTYPE (3-PISTON AXIAL CAM, BRASS HEAD TYPE (2-START & RUN DRY PROTECTION) (3-PISTON AXIAL CAM, BRASS HEAD (3-PISTON HIMIMUM (3-P		N/A	N/A	YES	
TYPE 3-PISTON AXIAL CAM, BRASS HEAD (EZ-START & RUN DRY PROTECTION) 250 HOUR MINIMUM 500 HOUR MINIMUM YES CHEMICAL INJECTOR LOW PRESSURE VENTURI CHASSIS WHEEL BARROW - 1-1/4 TUBING QUICK-RELASE FOLD-DOWN HANDLE 10" X3" FOAM FILLED RUBBER STEEL RIM POFILE PLASTIC RIM ADDITIONAL FEATURES HIGH PRESSURE HOSE TRIGGER/GUN ARRENG FORD TO HOUR MINIMUM ARRING GREY, M22 CONPECTION, STANDARD QC COUPLERS TRIGGER/GUN ARIEN SFROM ENTRY M22-M INLET, CHROME PLATED TUBING QC COUPLER CONNECTION, STANDARD QC COUPLER 3 STANDARD QC NOZZLES ("," 25", 40") QC COUPLER CONNECTION, STANDARD QC COUPLER ON-BOARD DETERBENT CONTAINERS HIGH PRESSURE NOZZLES SOAP SOAP BLASTEL SIPHONING HOSE WITH FILTER DIMENSION OVERALL LENGTH (INCHES) DOVERALL LENGTH (INCHES) DOVER PROVED THE PLANT OF TH		TT1	OAT D	IIMPO	
LIFE EXPECTANCY 150 HOUR MINIMUM 160 HOUR MINIMUM 170 HEELBARGW - 1-1/4 TUBING QUICK-RELEASE FOLD-DOWN HANDLE 160 TO AND FILLED RUBBER 160 TO AND HILLER RUBBER STEEL RIM 160 THE PLASTIC RIM 170 THE PLASTIC PURTUAL 170 THE PLA	MANUFACIUKEK		CALP	.OML2	
LIFE EXPECTANCY THERMAL RELIEF VALVE CHEMICAL INJECTOR LOW PRESSURE VENTURI CHASSIS WHEEL BARROW - 1-1/4 TUBING QUICK-RELEASE FOLD-DOWN HANDLE 10" X 3" FOAM FILLED RUBBER STEEL RIM ADDITIONAL FEATURES LI/4" X 25", PVC OUTER SKIN, YARN BRAIDED, NON-MARRING GREY, M22 COUPLERS TRIGGER/GUN ARIENS FRONT ENTRY, M22-M INLET, CHROME PLATED, M22 COUPLERS SPRAY WAND ARIENS FRONT ENTRY, M22-M INLET, CHROME PLATED, M22 COUPLERS SPRAY WAND 21" CHROME PLATED, M22 COUPLERS SOAP 21" STAINLESS STEEL, M22 CONNECT COUPLERS (0", 25", 40") ONE TOUCH QUICK CONNECT COUPLER SIPHONING HOSE WITH FILTER DIMERSION SIPHONING HOSE WITH FILTER DIMERSION ONE TOUCH QUICK CONNECT COUPLER SIPHONING HOSE WITH FILTER DIMERSION ONE TOUCH QUICK CONNECT COUPLER SIPHONING HOSE WITH FILTER DIMERSION OVERALL LENGTH (INCHES) OVERALL LENGTH (INCHES) DYEAL LENGTH (INCHES) OVERALL SEALER NOZZLE, POWER PLAYED, PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWER PLESS PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWER PLESS PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWER PLESS PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, NOZLE, SÓ-INE EXTENSION WAND, ROUTHER CLEANER, PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, NOZLE, SÓ-INE EXTENSION WAND, ROUTHER CLEANER, PRESSURE WASHER FOOVER WINDOW AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER FOOVER WINDOW AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER COVER	TYPE		CAT TRIPLEX,	BRASS HEAD	
CHEMICAL INJECTOR CHASSIS WHEEL BARROW - 1-1/4 TUBING QUICK-RELEASE FOLD-DOWN HANDLE IO" X.3" FOAM FILLED RUBBER STEEL RIM PROFILE PLASTIC RIM RUBBER STEEL RIM SHORT/HITCH-PIN AXLE SHORT/HITCH-PIN ADDITIONAL FEATURES I1/4" X.25", PVC OUTER SKIN, YARN BRAIDED, NON-MARRING GREY, M22 COUPLERS COUPLERS TRIGGER/GUN ARIENS FRONT ENTRY, M22-M INLET, CHROME PLATED TUBING QUICK CONNECT COUPLERS SPRAY WAND 21" CHROME PLATED, M22 CONNECTION, STANDARD QUE COUPLER SKIN, STEEL RIM RESSURE NOZZLES (0", 25", 40") ONE PRESSURE NOZZLES GON-BOARD DETERGENT SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER DIMERSION OVERALL HEIGHT (INCHES) OVERALL SIGN ON OVER PRESSURE WASHER MAINTEMANCE KIT, ON OVER PRESSURE WASHER MAINTEMANCE KIT, ON OVER PRESSURE WASHER MAINTEMANCE KIT, ON OVER PRESSURE WASHER MONTEMANCE KIT, ON OVER PRESSURE WASHER ROUSE, OPPORTS SUR WASHER GUNG ON OVER CHANCE, OF OTHER PRESSURE WASHER ROUSE, PROFESSIONAL GRADE TURBO NOZZLE, ON ON OVER AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER ROUSE, OF OWEN ON OVER PRESSURE WASHER ROUSE, OF OWEN ON OVER OWN ON OVER ON OVER OWN OWN OWN OWN ON OVER OWN	LIFE EXPECTANCY		500 HOUR MINIMUM		
CHARSSIS WHEEL BARROW - 1-1/4 TUBING QUICK-RELEASE FOLD-DOWN HANDLE FOLD-DOWN HANDLE FOLD-DOWN HANDLE FOLD-DOWN HANDLE STEEL RIM STEEL RIM STEEL RIM SHORT/HITCH-PIN SHORT/HI	THERMAL RELIEF VALVE				
FRAME STYLE WHEEL BARROW - 1-1/4 TUBING QUICK-RELEASE FOLD-DOWN HANDLE 10" X 3" FOAM FILLED RUBBER STEEL RIM SHORT/HITCH-PIN AXLE SHORT/HITCH-PIN SHORT/HITCH-PIN SHORT/HITCH-PIN SHORT/HITCH-PIN SHORT/HITCH-PIN SHORT/HITCH-PIN SHORT/HITCH-PIN ADDITIONAL FEATURES 1/4" X 25', PVC OUTER SKIN, YARN BRAIDED, NON-MARRING GREY, M22 COUPLERS COUPLERS TRIGGER/GUN ARIENS FRONT ENITRY, M22-M INLET, CHROME PLATED TUBING QUICK CONNECT COUPLERS CONNECTION, STANDARD QUE COUPLER 3 STANDARD QC NOZZLES (0", 25", 40") CONNECTION, STANDARD QUE COUPLER 3 STANDARD QC NOZZLES (0", 25", 40") SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER DIMENSION OVERALL LENGTH (INCHES) OVERALL SIDHON AND SIDHON AND SIDHON BROSEWER WASHER MOSZIE, TWO-POSITION SOAP APPLICATOR NOZZIE, 36-IN EXTENSION WAND, ONTAINS BRUSHS, IT TELSCOPINE MSHER ROOZZIE, TWO-POSITION SOAP APPLICATOR NOZZIE, 36-IN EXTENSION WAND, ONTAINS BRUSHS, IT TELSCOPINE MSHER ROOZZIE, TWO-POSITION SOAP APPLICATOR NOZZIE, 36-IN EXTENSION WAND, ONTAINS BRUSHS, IT TELSCOPINE MSHER ROOZZIE, TWO-POSITION SOAP APPLICATOR NOZZIE, 36-IN EXTENSION WAND, ONTAINS BRUSHS, IT TELSCOPINE MSHER ROOZZIE, TWO-POSITION SOAP APPLICATOR NOZZIE, 36-IN EXTENSION WAND, ONTAINS BRUSHS, IT TELSCOPINE MSHER ROOZZIE, TWO-POSITION SOAP APPLICATOR NOZZIE, 36-IN EXTENSION WAND, ONTAINS BRUSHS, IT TELSCOPINE MSHER GOVER	CHEMICAL INJECTOR	LOW PRESSURE VENTURI	LOW PRESSU	JRE VENTURI	
FRAME STYLE QUICK-RELEASE FOLD-DOWN HANDLE 10" X 3" FOAM FILLED RUBBER STEEL RIM SHORT/HITCH-PIN AXLE SHORT/HITCH-PIN S	CHASSIS				
MREEL TYPE STEEL RIM SHORT/HITCH-PIN SHANDED JERGER/SUN ARIENS FRONT ENTRY, M22-M INLET, CHROME PLATED TUBING COUPLERS SPRAY WAND 21" CHROME PLATED TUBING 21" CHROME PLATED TUBING, OVER-MOLD GRIP AREAS, REMOVABLE ASSIST HANDLE 21" CHROME PLATED, M22 CONNECTION, STANDARD QC COUPLER 3 STANDARD QC NOZILES 3 QUICK CONNECT NOZILES 3 QUICK CONNECT NOZILES 4 QUICK CONNECT NOZILES (0°, 25°, 40°) CONTAINER/BOTTLE HOLDER ON-BOARD DETERGENT CONTAINER/BOTTLE HOLDER SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER DIMER/SION OVERALL LENGTH (INCHES) 36" 26" OVERALL LENGTH (INCHES) 36" 26" OVERALL HEIGHT (INCHES) 36" 36" 32" OVERALL HEIGHT (INCHES) 36" 36" 36" 36" 36" 37" 30" 30" 30" 30" 30" 30" 30	FRAME STYLE	QUICK-RELEASE	ROLL-CAGE -1-1/4 TUBING QUICK-RELEASE FOLD-DOWN HANDLE		
ADDITIONAL FEATURES I 1/4" X 25', PVC OUTER SKIN, YARN BRAIDED, NON-MARRING GREY, M22 COUPLERS I 1/4" X 25', PVC OUTER SKIN, YARN BRAIDED, NON-MARRING GREY, M22 COUPLERS I 1/4" X 25', PVC OUTER SKIN, YARN BRAIDED, NON-MARRING GREY, M22 COUPLERS I 1/4" X 25', PVC OUTER SKIN, YARN BRAIDED, SEMI-TRANSLUCENT TITANIUM, 3/8" QUICK CONNECT COUPLERS I 1/4" X 25', PVC OUTER SKIN, YARN BRAIDED, SEMI-TRANSLUCENT TITANIUM, 3/8" QUICK CONNECT COUPLERS I 1/4" X 25', PVC OUTER SKIN, YARN QUICK CONNECT COUPLERS I 1/4" X 25', PVC OUTER SKIN, YARN QUICK CONNECT COUPLERS I 1/4" X 25', PVC OUTER SKIN, YARN QUICK CONNECT COUPLERS I 1/4" X 25', 40" ARIA CONNECT COUPLERS I 1/4" X 25', PVC OUTER SKIN, YARN QUICK CONNECT COUPLERS I 1/4" X 25', 40" ARIA CONNECT COUPLERS I 1/4" X 25', PVC OUTER SKIN, YARN QUICK CONNECT PLUG INLET, CHROME PLATED TUBING, OVER-MOLD GRIP AREAS, REMOVABLE ASSIST HANDLE I 1/4" X 25', 40" ARIA CONNECT COUPLERS I 1/4" X 25', 40" ARIA CONNECT COUPLERS I 21" STAINLESS STEEL, M22 CONNECTION, ONE TOUCH QUICK CONNECT NOZZLES (0°, 25°, 40°) I 1/4" X 25', 40" ARIA CONNECT COUPLERS I 21" STAINLESS STEEL, M22 CONNECT NOZZLES (0°, 25°, 40°) I 2 1/4" X 25', 40" ARIA CONNECT COUPLER I 2 1/4" X 25', 40" ARIA CONNECT COUPLER I 2 1/4" X 25', 40" ARIA CONNECT COUPLER I 2 1/4" X 25', 40" ARIA CONNECT COUPLER I 2 1/4" ARIA CONNECT COUPLER	WHEEL TYPE				
HIGH PRESSURE HOSE 1/4" X 25', PVC OUTER SKIN, YARN BRAIDED, NON-MARRING GREY, M22 COUPLERS 1/4" X 25', PVC OUTER SKIN, YARN BRAIDED, NON-MARRING GREY, M22 COUPLERS 1/4" X 25', PVC OUTER SKIN, YARN BRAIDED, NON-MARRING GREY, M22 COUPLERS 1/4" X 25', PVC OUTER SKIN, YARN BRAIDED, SEMI-TRANSLUCENT TITANIUM, 3/8" QUICK CONNECT COUPLERS 1/4" X 25', PVC OUTER SKIN, YARN QUICK CONNECT COUPLERS 1/4" X 25', PVC OUTER SKIN, YARN QUICK CONNECT COUPLERS 1/4" X 25', AVC OUTER SKIN, YARN QUICK CONNECT COUPLERS 1/4" X 25', AVC OUTER SKIN, YARN QUICK CONNECT COUPLERS 1/4" CHROME PLATED TUBING 1/4" X 25', AVC OUTER SKIN, YARN QUICK CONNECT COUPLERS 1/4" X 25', AVC OUTER SKIN, STE BRAIDED, SEMI-TRANSLUCENT TITANIUM, 3/8" QUICK CONNECT PLUG INLET, CHROME PLATED TUBING, OVER-MOLD GRIP AREAS, REMOVABLE ASSIST HANDLE 1/4" X 25', AVC OUTER SKIN, YARN QUICK CONNECT PLUG INLET, CHROME PLATED TUBING, OVER-MOLD GRIP AREAS, REMOVABLE ASSIST HANDLE 1/4" X 25', AVC OUTER SKIN, YARN QUICK CONNECT COUPLERS 1/4" X 25', AVC OUTER SKIN, YARN QUICK CONNECT PLUG INLET, CHROME PLATED TUBING, OVER-MOLD GRIP AREAS, REMOVABLE ASSIST HANDLE 1/4" X 25', AVC OUTER SKIN, YARN QUICK CONNECT PLUG INLET, CHROME PLATED TUBING, OVER-MOLD GRIP AREAS, REMOVABLE ASSIST HANDLE 1/4" X 25', AVC OUTER SKIN, STEEL BRAIDED CONNECT NOZZLE SEMI-TRANSLUCENT TITANIUM, 3/8" QUICK CONNECT PLUG INLET, CHROME PLATED ONE COUTER SITE AND A SUICK CONNECT OUTER SITE BRAIDED CONNECT NOZZLE, TWO-POSITION SOAP APPLICATION NOZZLE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18" TELESCOPING WAND, 9' EXTENSION WAND, WINDOW AND SIDING BRUSH, BUTTER CLEANER, PRESSURE WASHER COVER	AXLE	SHORT/HITCH-PIN	SHORT/H	ITCH-PIN	
HIGH PRESSURE HOSE 14" X 29", PVC UUIER SXIN, YARN BRAIDED, NON-MARRING GREY, M22 COUPLERS 17" STAINLESS FRONT ENTRY, M22-M INLET, CHROME PLATED TUBING COUPLERS 21" CHROME PLATED TUBING COUPLER COUPLER COUPLERS CONNECT COUPLERS 21" CHROME PLATED, M22 CONNECTION, STANDARD OC COUPLER COUPLE COUPLER COUPLE COUPLER COUPLE	ADDITIONAL FEATURES			1	
CHROME PLATED TUBING 21" CHROME PLATED, M22 CONNECTION, STANDARD OC COUPLER 3 STANDARD QC COUPLER 3 STANDARD QC COUPLER 3 STANDARD QC COUPLER 3 STANDARD QC COUPLER 3 QUICK CONNECT NOZZLES (0°, 25°, 40°) (0°, 25°, 40°) (0°, 25°, 40°) (0°, 25°, 40°) (0°, 25°, 40°) 1 QUICK CONNECT COUPLER 3 QUICK CONNECT NOZZLES (0°, 25°, 40°) (0°, 25°, 40°) 1 QUICK CONNECT NOZZLES 2 QUICK CONNECT NOZZLES 3 QUICK CONNECT NOZZLES 3 QUICK CONNECT NOZZLES (0°, 25°, 40°) 3 QUICK CONNECT NOZZLES 3 QUICK CONNECT NOZZLES (0°, 25°, 40°) 3 QUICK CONNECT NOZZLES 3 QUICK CONNECT NOZZLES (0°, 25°, 40°) 4 QUICK CONNECT NOZZLES (0°, 25°, 40°) (0°, 25°, 40°) 5 QUERALE ROZZLE HOLDER 5 QUERALE LENGTH (INCHES) 5 QUERALL HEIGHT (INCHES) 5 QUERALL HEIGHT (INCHES) 6 QUERALL HEIGHT (INCHES) 7 QUERALL HEIGHT (INCHES) 7 QUERALL HEIGHT (INCHES) 6 QUERALL HEIGHT (INCHES) 7 QUERALL HEIGHT (INCHES) 7 QUERALL HEIGHT (INCHES) 6 QUERALL HEIGHT (INCHES) 7 QUERALL HEIGHT (INCHES) 7 QUERALL HEIGHT (INCHES) 7 QUERALL HEIGHT (INCHES) 8 QUERALL HEIGHT (INCHES) 9 QUERALL HEIGHT (INCHES) 9 QUERALL HEIGHT (INCHES) 10 QUERALL HEIGHT (INCHES) 11 QUERAL WASHER MAINTENANCE KIT, 12 QUERAL HEIGHT (INCHES) 13 QUERAL HEIGHT (INCHES) 14 QUERAL MURCH (INCHES) 15 QUERAL HEIGHT (INCHES) 16 QUERAL WASHER MAINTENANCE KIT, 17 QUERAL HEIGHT (INCHES) 18 QUERAL HEIGHT (INCHES) 19 QUERAL HEIGHT (INCHES) 10 Q	HIGH PRESSURE HOSE	BRAIDED, NON-MARRING GREY, M22		BRAIDED, SEMI-TRANSLUCENT TITANIUM, 3/8" QUICK CONNECT	
SPRAY WAND CONNECTION, STANDARD OC COUPLER AS STANDARD OC NOZZLES (0°, 25°, 40°) LOW PRESSSURE NOZZLES (0°, 25°, 40°) LOW PRESSSURE NOZZLES SOAP SOAP SOAP SOAP BLASTER ON-BOARD DETERGENT CONTAINER/BOTTLE HOLDER DIMENSION OVERALL LENGTH (INCHES) OVERALL WIDTH (INCHES) 26" OVERALL HEIGHT (INCHES) DRY WEIGHT (LBS) G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWERFLEX PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 36-INE EXTENSION WAND, ROTATING BRUSH, 18" TELESCOPING WAND, 9" EXTENSION WAND, WINDOW AND SIDING BRUSH, 18" TELESCOPING WASHER COVER	TRIGGER/GUN				
LOW PRESSURE NOZZLES (0°, 25°, 40°) (0°, 25°, 40°) (0°, 25°, 40°) (0°, 25°, 40°) (0°, 25°, 40°) (0°, 15°, 40°) (0°, 15°, 40°) (1°, 25°, 40°) (1°, 25°, 40°) (1°, 25°, 40°) (1°, 25°, 40°) (1°, 25°, 40°) (1°, 25°, 40°) (1°, 25°, 40°) (1°, 15°, 25°, 40°) (1°, 15°, 25°, 40°) (1°, 15°, 25°, 40°) (1°, 15°, 25°, 40°) (1°, 15°, 25°, 40°) (1°, 15°, 25°, 40°) (1°, 15°, 25°, 40°) (1°, 15°, 25°, 40°) (1°, 15°, 25°, 40°) (1°, 15°, 25°, 40°) (1°, 15°, 25°, 40°) (2°, 10°, 10°, 10°, 10°, 10°, 10°, 10°, 10	SPRAY WAND	CONNECTION, STANDARD			
REMOVABLE NOZZLE HOLDER ON-BOARD DETERGENT CONTAINER/BOTTLE HOLDER SIPHONING HOSE WITH FILTER DIMENSION OVERALL LENGTH (INCHES) 26" OVERALL HEIGHT (INCHES) 26" 22" OVERALL HEIGHT (INCHES) 75 98 105 ACCESSORIES G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWERFLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, 15" SURFACE CLEANER, 50" STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPRAY NOZZLE, CONSUMER GRADE TURBO NOZZLE, TWO-POSITION SOAP APPLICATION NOZZLE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18" TELESCOPING WAND, 9' EXTENSION WAND, WINDOW AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER COVER	HIGH PRESSURE NOZZLES				
ON-BOARD DETERGENT CONTAINER/BOTTLE HOLDER SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER SIPHONING HOSE WITH FILTER DIMENSION OVERALL LENGTH (INCHES) OVERALL LENGTH (INCHES) 24" 22" OVERALL HEIGHT (INCHES) 26" 21" DRY WEIGHT (LBS) 75 98 105 ACCESSORIES G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWERFLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, 15" SURFACE CLEANER, 50" STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPOR'S TEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPOR'S TEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPOR'S TEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPOR'S TEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPOR'S TEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPOR'S TEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPOR'S TEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPOR'S TEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPOR'S TEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, TWO-POSITION SOAP APPLICATION NOZZLE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18" TELESCOPING WAND, 9" EXTENSION WAND, WINDOW AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER COVER					
CONTAINER/BOTTLE HOLDER DIMENSION OVERALL LENGTH (INCHES) OVERALL WIDTH (INCHES) OVERALL HEIGHT (INCHES) OVERALL HEI		NO	YES		
DIMENSION OVERALL LENGTH (INCHES) 36" 26" OVERALL WIDTH (INCHES) 24" 22" OVERALL HEIGHT (INCHES) 26" 21" DRY WEIGHT (IRCHES) 75 98 105 ACCESSORIES G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWERFLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, 15" SURFACE CLEANER, 50" STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLI, 6-IN-1 CHANGEOVER SPOYS TEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLI, 6-IN-1 CHANGEOVER SPOYS TO STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSION GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPOYS TO STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSION USAND, 9" EXTENSION WAND, NOTATING BRUSH, 18" TEUR NOZZLE, TWO-POSITION SOAP APPLICATION NOZZLE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18" TEUR NOZZLE TWO-POSITION SOAP APPLICATION NOZZLE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18" TEUR NOZZLE TWO-POSITION SOAP APPLICATION NOZZLE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18" TEUR NOZZLE WASHER COVER		SIPHONING HOSE WITH FILTER	SIPHONING HO	SE WITH FILTER	
OVERALL LENGTH (INCHES) OVERALL WIDTH (INCHES) 24" 22" OVERALL HEIGHT (INCHES) 26" 21" DRY WEIGHT (LBS) 75 98 105 ACCESSORIES G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZILE, POWERRLEY PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GOVZ, 15" SURFACE CLEANER, 50" STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZILE, 6-IN-1 CHANGEOVER SPRAY NOZZILE, CONSUMER GRADE TURBO NOZZILE, TWO-POSITION SOAP APPLICATOR NOZZILE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18" TELESCOPING WAND, 9" EXTENSION WAND, WINDOW AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER COVER					
OVERALL WIDTH (INCHES) 24" 22" OVERALL HEIGHT (INCHES) 26" 21" DRY WEIGHT (LBS) 75 98 105 ACCESSORIES G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZIE, POWERRELY PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, 15" SURFACE CLEANER, 50' STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZIE, G-IN-1 CHANGEOVER SPRAY NOZZIE, CONSUMER GRADE TURBO NOZZIE, TWO-POSITION SOAP APPLICATOR NOZZIE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18' TELESCOPING WAND, 9' EXTENSION WAND, WINDOW AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER COVER		36"	2.	6"	
OVERALL HEIGHT (INCHES) 26" 21" DRY WEIGHT (LBS) 75 98 105 ACCESSORIES G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZILE, POWERRLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, 15" SURFACE CLEANER, 50' STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZIL G-IN-1 CHANGEOVER SPRAY NOZZIE, CONSUMER GRADE TURBO NOZZIE, TWO-POSITION SOAP APPLICATOR NOZZIE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18' TELESCOPING WAND, 9' EXTENSION WAND, WINDOW AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER COVER					
DRY WEIGHT (LBS) 75 98 105 ACCESSORIES G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWERFLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, 15" SURFACE CLEANER, 50" STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE, 6-IN-1 CHANGEOVER SPRAY NOZZLE, CONSUMER GRADE TURBO NOZZLE, TWO-POSITION SOAP APPLICATOR NOZZLE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18" TELESCOPING WAND, 9" EXTENSION WAND, WINDOW AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER COVER					
G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWERFLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, 15° SURFACE CLEANER, 50' STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE 6-IN-1 CHANGEOVER SPRAY NOZZLE, CONSUMER GRADE TURBO NOZZLE, TWO-POSITION SOAP APPLICATOR NOZZLE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18' TELESCOPING WAND, 9' EXTENSION WAND, WINDOW AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER COVER			_		
G-CLEAN SIDING AND GENERAL PURPOSE CLEANER, G-PUMP PRESSURE WASHER MAINTENANCE KIT, G-SEAL SEALER NOZZLE, POWERFLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, 15" SURFACE CLEANER, 50" STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE 6-IN-1 CHANGEOVER SPRAY NOZZLE, CONSUMER GRADE TURBO NOZZLE, TWO-POSITION SOAP APPLICATOR NOZZLE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18" TELESCOPING WAND, 9" EXTENSION WAND, WINDOW AND SIDING BRUSH, GUTTER CLEANER, PRESSURE WASHER COVER		13	30	103	
		G-SEAL SEALER NOZZLE, POWERFLEX PRESSURE WASHER HOSE, CAT HEAVY-DUTY PRESSURE WASHER GUN, 15" SURFACE CLEANER, 50" STEEL BRAIDED PRESSURE WASHER HOSE, PROFESSIONAL GRADE TURBO NOZZLE G-IN-1 CHANGEOVER SPRAY NOZZLE, CONSUMER GRADE TURBO NOZZLE, TWO-POSITION SOAP APPLICATOR NOZZLE, 36-IN EXTENSION WAND, ROTATING BRUSH, 18" TELESCOPING WAND, 9" EXTENSION WAND,			
	WADDANTY	0.01	. ,		

	STRING TRIMMER	R & EDGER	
PRODUCT NAME	STRING TRIMMER	EDGER	EDGER
MODEL NUMBER	946152	986101	986103
ENGINE	KOHLER® XT-775	SUBARU®	ARIENS AX
HORSEPOWER / Displacement (CC)	4.5 HP / 173CC	169 CC	136 CC
STARTING SYSTEM	RECOIL	RECOIL	RECOIL
DRIVE SYSTEM	PUSH	PUSH	PUSH
FUEL CAPACITY	0.37 GALLON (1.4L)	0.71 GALLON (2.6L)	0.71 GALLON (2.6L)
DECK			
DECK MATERIAL	14 GA	12 GA	12 GA
DECK CONSTRUCTION	STAMPED	FORMED	FORMED
NUMBER OF SPINDLES	1	1	1
BLADE DIAMETER	N/A	9 INCH	9 INCH
SPINDLE MATERIAL	N/A	STEEL	STEEL
SPINDLE SHAFT	N/A	1/2" DIA. STEEL	1/2" DIA. STEEL
SPINDLE BEARINGS	N/A	SEALED	SEALED
DECK DRIVE	BELT	BELT	BELT
CUT ANGLE	N/A	110 DEGREES	110 DEGREES
CUT POSITIONS	4	4	4
CUTTING WIDTH	22" W/15° SWIVEL TO THE LEFT AND RIGHT	N/A	N/A
CUTTING HEIGHTS	1.25" - 4.25"	N/A	N/A
OPERATOR SAFETY LEVER	N/A	YES	YES
WHEELS			
WHEEL DIAMETER	N/A	8"	8"
WHEEL BEARINGS	N/A	YES	YES
DROP WHEEL FOR CURB	N/A	YES	YES
FRONT AXLE	N/A	LATERALLY ADJUSTABLE	LATERALLY ADJUSTABLE
FRONT	N/A	1.75" X 7.5"	1.75" X 7.5"
REAR	14"	1.75" X 7.5"	1.75" X 7.5"
DIMENSIONS			
WEIGHT (LBS)	83	72	72
LENGTH	58"	44.75"	44.75"
WIDTH	22"	19.75"	19.75"
HEIGHT	41"	38"	38"
WARRANTY			
MACHINE	3-YEAR LIMITED CONSUMER / 90-DAY LIMITED COMMERCIAL		

	WALK-BEHIND VACUUM		
PRODUCT NAME	APV		
MODEL NUMBER	995051	995049	
ENGINE			
MANUFACTURER	SUBARU®	SUBARU®	
HORSEPOWER/ DISPLACEMENT	5.5 HP/190CC	5.5 HP/190CC	
STARTING SYSTEM	RECOIL	RECOIL	
FUEL CAPACITY	0.32 GAL (1.2 L)	0.32 GAL (1.2 L)	
KEY FEATURES			
DRIVE SYSTEM	PUSH	SELF-PROPELLED	
INTAKE	31" (78.7 CM)	31" (78.7 CM)	
FAN HOUSING	12 GA STEEL	12 GA STEEL	
IMPELLER	13.5" STEEL, 5-BLADE, SERRATED	13.5" STEEL, 5-BLADE, SERRATED	
CFM	1775	1775	
DEBRIS REDUCTION RATIO	12:1	12:1	
DEBRIS DEFLECTOR	STANDARD	STANDARD	
HANDLE	RITE-HITE 1" TUBULAR STEEL - 3 OPERATING POSITIONS, 2 STORAGE POSITIONS		
COLLECTION BAG	POLY FELT	POLY FELT	
COLLECTION CAPACITY	6 CU FT	6 CU FT	
WHEELS			
FRONT	14" SOLID	14" SOLID	
REAR	14" SOLID	14" SOLID	
DIMENSIONS			
LENGTH (IN.)	53" (134.6 CM)	53" (134.6 CM)	
WIDTH (IN.)	31" (78.7 CM)	31" (78.7 CM)	
HEIGHT (IN.)	48" (121.9 CM)	48" (121.9 CM)	
DRY WEIGHT (LBS.)	152 (69 KG)	170 (77 KG)	
ACCESSORIES/ATTACHMENTS			
	NYLON MESH BAG, 7' HOSE KIT		
WARRANTY			
MACHINE	1-YEAR LIMITED CONSUMER / 1-YEAR LIMITED COMMERCIAL		



KOHILER 7000 SERIES 20-26 HP

KOHLER. Engines

A V-TWIN BEAST FOR WEEKEND WARRIORS

Want an engine as durable and fully loaded as the pros? Now you've got it with the KOHLER, air-cooled, V-twin 7000 Series, engine, Power up your tractor or ZTR and run rings around your neighbors with pro-grade features, easy starts, durable components and powerful cuts.

JUST TURN THE KEY AND GO

- No need to manually adjust the throttle or choke.
- Optional Smart-Choke. (based on OEM) makes starting easy just turn the key and go.
- High-torque inertia drive starter with extra-large output for quick, reliable starting.

BUILT TO LAST

- Dual-seal air filter keeps debris out of the engine.
- Cast iron cylinder bores protect under dirty conditions.
- Pressure lubrication extends engine life.

SUPERIOR CUTS

 Consistent-Cut. technology provides more consistent power to your deck to help you get the perfect cut.

PRO-GRADE PERFORMANCE

- Optional PRO Performance air, oil and fuel filters deliver maximum performance.
- Top models feature more power through higher displacement* and variable-speed ignition.**

EASY MAINTENANCE

- Easy-access air filter allows for quick inspection and maintenance.
- Highlighted service points on same side of engine for convenient servicing.

Models KT740 and KT745.

For more information, contact your KOHLER source of supply. Or call toll-free in the U.S. and Canada 800-544-2444.

Kohler Co., Kohler, Wisconsin 53044 Tel 920-457-4441 Fax 920-459-1570

KohlerEngines.com

KOHLER Engines

Passionate People. Astounded Customers.

Visit your local dealer to learn more about the extensive, high-performance lineup of Ariens Lawn & Garden and Sno-Thro® products.



Find Product Information

Read Customer Reviews

Locate an Authorized Dealer

View Ariens Product Videos



Scan with mobile device for additional Ariens product information



© 2015 Ariens Company. All rights reserved. ® Registered trademark and ™ trademark of Ariens Company. Briggs & Stratton®, Kohler®, Kawasaki® and Subaru® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only.

Actual operating horsepower will be less. Visit *www.ariens.com* for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.

An **Ariens** Company Brand