

CHAIN LUBE OIL WITH CERFLON®

L704, L706, L711



PVC Bottle, 4 oz.
078698217475

Aerosol Metal, 5.5 oz.
078698217369

Aerosol Metal, 11 oz.
078698217345

LIQUID WRENCH® High-Performance Dry Lubricant with CERFLON® is a long-lasting dry film lubricant that cuts friction, helps extend life and protects against wear. Leaves no oily residue.

APPLICATIONS:

- Apply To Any Chain Or Wire Cable
- Stays Put On Moving Parts, Reduces Friction
- Reduces Wear & Noise

DIRECTIONS: Shake well. Spray on areas to lubricate. Allow solvent to evaporate. Get Material Safety Data Sheet via liquidwrench.com.

STORAGE, HANDLING & DISPOSAL: Do not expose to heat, sparks or flames. Store in dry, well-ventilated area below 120°F/49°C. Do not puncture, crush or incinerate can. Dispose of product, container and residue according to all local, state and federal laws and regulations.

DANGER: EXTREMELY FLAMMABLE. FIRE AND EXPLOSION HAZARD: Use only in a well-ventilated area away from heat, sparks, and flames. Do not place container in contact with hot surfaces, batteries or electrical current, because of risk of violent bursting and flash fire. Use added caution in confined areas such as basements and automobile compartments. **Breathing & INGESTION HAZARDS:** INHALING CONCENTRATED VAPORS INTENTIONALLY OR OTHERWISE MAY CAUSE DEATH WITHOUT WARNING. Harmful or fatal if swallowed. **CONTACT HAZARD:** Eye irritant. Prolonged skin contact may cause dermatitis.

FIRST AID: EYE CONTACT: Flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. **SKIN CONTACT:** Wash with soap and water. If irritation develops, get prompt medical attention. **INHALATION:** Move to fresh air. If breathing becomes difficult, get prompt medical attention. **INGESTION:** DO NOT INDUCE VOMITING. Call Poison Control Center, Physician or Hospital Emergency Room immediately.

CERFLON® is a registered trademark and brand owned by CERAMIC REINFORCED TECHNOLOGIES.

KEEP AWAY FROM CHILDREN AND ANIMALS

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.