# **DUPONT<sup>™</sup> PROSHIELD<sup>®</sup> BASIC GARMENTS**

Comfort and quality design at an affordable price.

# Comfort, quality and value come together in DuPont<sup>Th</sup> ProShield<sup>®</sup> Basic

New DuPont<sup>™</sup> ProShield<sup>®</sup> Basic garments make it easier than ever to provide your workers with a comfortable, quality coverall for those dirty work assignmentswhile enabling you to cut costs for disposable garments. These spunbond meltblown spunbond (SMS) garments are made to the high quality standards you have come to expect from DuPont.

## Comfort fit design helps workers get the iob done

Soft, breathable and lightweight, DuPont<sup>™</sup> ProShield<sup>®</sup> Basic garments feature a proprietary DuPont comfort fit design that is specially engineered for enhanced worker range of motion and durability in use.

Now, with DuPont<sup>™</sup> ProShield<sup>®</sup> Basic garments, workers performing general maintenance, janitorial/cleaning and other dirty work can be more comfortable while being protected from dirt, grime and non-hazardous dry particles.

# Garments designed to meet your needs

DuPont<sup>™</sup> ProShield<sup>®</sup> Basic garments are available in a variety of coverall styles in a choice of blue or white, in sizes ranging from medium to 5XL.

## For more information about DuPont<sup>™</sup> ProShield<sup>®</sup> Basic garments, contact your DuPont Customer Service Representative.

www.PersonalProtection.DuPont.com United States 1-800-931-3456 Canada 1-800-387-9326



# DuPont<sup>™</sup> SafeSPEC<sup>™</sup>2.0

## www.SafeSPEC.DuPont.com

#### DISCLAIMER:

#### coverall

PB 120 S BU xx 0025 00				
open v	vrists	and a	1	
open a	ınkles	A	2	
		ET THE	6	
MD	40K998	AY COULD	V	
LG	40K999	2 60180	1	
XL	40L001	SIL		
2X	40L002	100	1	
3X	40L003			
4X	40L004	12 13		
5X	40L005			

#### coverall

1
2
A.
ų

#### coverall

	25 S BU xx 0 c wrists	025 00		
elastic ankles				
MD	40L027			
LG	40L028			
XL	40L029			
2X	40L030			
3X	40L031			
4X	40L032			
5X	40L033			

#### coverall

PB 127 S BU xx 0025 00 attached hood elastic ankles					
MD LG XL 2X 3X 4X 5X	40L041 40L042 40L043 40L044 40L045 40L046 40L047	Ø			



### coverall

PB 120 S WH xx 0025 00					
open wrists					
open ankles					
		(1966) (1966)			
MD	40L006	1 85 N			
LG	40L007				
XL	40L008				
2X	40L009				
3X	40L010	And Mark			
4X	40L011	1 1			
5X	40L012	Se 13			
		Taula Para			

#### coverall

attac	22 S WH xx 0025 00 hed hood	0
	hed skid-resistant	A COL
boots	5	101 - 0
	62	MAG
MD	40L020	Yes a
LG	40L021	011
XL	40L022	633 C
2X	40L023	M AGE
3X	40L024	10.0 852
4X	40L025	10 10
5X	40L026	(III V)
		8 4

#### coverall



#### coverall



#### WARNINGS:

1) ProShield<sup>®</sup> Basic garments are not flame-resistant and should not be used around heat, flame. sparks or in potentially flammable or explosive environments.

2) Garments made of ProShield® should have slip-resistant or antislip materials on the outer surface of boots, shoe covers or other garment surfaces in conditions where slipping could occur.

This information is based upon technical data that DuPont believes to be reliable. It is subject to revision as additional knowledge and experience are gained. DuPont makes no guarantee of results and assumes no obligation or liability in connection with this information. It is the user's responsibility to determine the nature and level of hazards and the proper personal protective equipment needed. The information set forth herein reflects laboratory performance of fabrics, not complete garments, under controlled conditions. It is intended for information use by persons having technical skill for evaluation under their specific end-use conditions, at their own discretion and risk. Anyone intending to use this information should first verify that the garment selected is suitable for the intended use. In many cases, seams and closures have shorter breakthrough times and higher penetration rates than the fabric. Please contact DuPont for specific data. These garments are intended for limited use and should be disposed of after single use. If fabric becomes torn, abraded or punctured, or if seams or closures fail, or if attached gloves, visors, etc. are damaged, end user should discontinue use of garment to avoid potential exposure.

Copyright © 2013 DuPont. All rights reserved. The DuPont Oval Logo, DuPont", The miracles of science", SafeSPEC" and ProShield" are trademarks or registered trademarks of E.I. du Pont de Nemours and Company or its affiliates. (11/13)