

HYDRAULIC JACK OIL

M3312, M3332, M3334



For use in all hydraulic jacks, snow plows and refillable shock absorbers. Intermixes completely with all other standard hydraulic jack fluids.

APPLICATIONS:

- Formulated With Extreme Pressure Additives

DIRECTIONS: To keep foreign matter from entering fluid chamber, wipe fill plug and area around it before removing plug from chamber. Follow manufacturer's recommendations for proper fill level. Keep fill at maximum level at all times. To keep hydraulic equipment in good condition, periodically drain system and refill with fresh liquid. **CAUTION:** Do not use in hydraulic brake systems or automatic transmissions.

STORAGE, HANDLING & DISPOSAL: Dispose of product, residue and the empty container in accordance with all local, state and federal laws and regulations.

DANGER: Do not take internally. Harmful if swallowed. Eye & skin irritant. Get Material Safety Data Sheet via liquidwrench.com.

FIRST AID: EYES: Flush thoroughly with water for 15 minutes while lifting eyelids and get prompt medical attention. **SKIN:** Wash with soap and water. If irritation persists, get prompt medical attention. **INGESTION:** If swallowed, **DO NOT INDUCE VOMITING.** Call Poison Control Center, physician or hospital emergency room immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS

Plastic Bottle, 12 fl. oz.
078698822136

Plastic Bottle, 32 fl. oz.
078698133331

Plastic Bottle, 1 gal.
078698133348

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.