



Plastic Bottle, 14.5 fl. oz.
078698821054

STOP SMOKIN'

M5714/6

Older engines tend to burn more oil than newer engines, resulting in excessive exhaust smoke. Oil burning and smoking occurs when motor oil enters the combustion chamber and burns along with the fuel. Called, "oil blow-by," this often occurs when continual friction has worn parts and created gaps between the cylinder walls, piston rings, and valve guide seals. This treatment forms a more viscous (thicker) oil cushion to help fill these gaps to reduce oil blow-by, excessive smoking, stops minor oil leaks, reduces oil consumption and smoking; cushions noisy valves and lifters; conditions oil seals.

APPLICATIONS:

- Helps Revive Seals & Gaskets
- Conditions Oil Seals
- Cushions Noisy Valves & Lifters
- Reduces Oil Consumption & Exhaust Smoking

DIRECTIONS: Warm up engine to operating temperature then pour into crankcase. Add one bottle at the time of, or between oil changes when oil level is down a quart. Compatible with conventional and synthetic motor oils. If oil leaks persist beyond 1,000 miles, mechanical repairs may be required.

STORAGE, HANDLING & DISPOSAL: Store in a cool, dry, well-ventilated area away from heat, sparks or open flames. Dispose of product, residue and container in accordance with all local, state, and federal laws and regulations.

DANGER: EYE IRRITANT. Use with adequate ventilation. Avoid sparks and flames. Avoid eye, skin contact and breathing vapors.

FIRST AID: For EYE CONTACT: rinse with water for 15 minutes while lifting eyelids and get prompt medical attention. For SKIN CONTACT: wash with soap and water promptly. INGESTION: If swallowed, DO NOT induce vomiting. Call Poison Control Center, Physician or Hospital Emergency Room Immediately.

KEEP AWAY FROM CHILDREN AND ANIMALS

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.